



TELECOM REGULATORY AUTHORITY OF INDIA

Independent Drive Test Report

North East LSA

March 2025

Contents

1. Introduction	3
2. Executive Summary (LSA)	3
2.1 Drive test details	3
2.2 Drive test routes	4
2.3 Summary of areas covered	4
2.4 Telecom service providers detected frequency bands	5
2.5 Performance against key QoS parameters	5
3. QoS performance analysis- LSA level	7
3.1 Overview	7
3.2 Voice performance	7
3.3 Data performance	9
4. Detailed QoS performance analysis	12
4.1 Overview	12
4.2 City	12
4.2.1 Drive test route	12
4.2.2 Areas covered	12
4.2.3 Voice performance	12
4.2.4 Data performance	20
4.3 Hotspots	22
4.3.1 Locations	22
4.3.2 Hotspot covered	22
4.3.3 Voice performance	22
4.3.4 Data performance (Auto-selection mode 5G/4G/3G/2G)	24
4.3.5 Data performance (5G Only & 4G Only Download & Upload Speed)	26
4.4 Walk Test	28
4.4.1 Locations	28
4.4.2 Walk Test Covered	28
4.4.3 Voice Performance	28
4.4.4 Data Performance	31
5. Voice & Data Key findings	33
5.1 Overall Voice	33
5.2 Overall Data	33
5.3 Operator wise Key Findings	34
6. Annexure	39

6.1 Route wise coverage map	39
6.1.1 City	39
7. Appendix	43
7.1 Appendix-I	43
7.1.1 Drive test setup	43
7.1.2 Drive test Methodology	45
7.2 Appendix-II	47
7.2.1 Network Performance Parameters for Voice calls	47
7.2.2 Network Performance Parameters Data tests	48

1. Introduction

TRAI Act, 1997 mandates the Authority to ensure the services delivered through various telecommunications networks meet required quality standards prescribed, to protect the interest of the consumers of telecommunication services. TRAI is also responsible for conducting the periodical audit of such services provided by the service providers so as to protect the interest of the consumers of telecommunications service.

Accordingly, TRAI has engaged M/s RedMango Analytics Pvt. Ltd. to undertake assessment of Quality of Service of mobile service through Independent Drive Test (IDT).

In IDT, the performance of all service providers providing service in a Licensed Service Area (LSA) through various technologies (like 2G/ 3G/ 4G/ 5G) for voice and data are measured by conducting drive test. The drive test routes are finalised based on various objective criteria like reported network performance, consumer complaints etc. Methodology adopted for conducting IDT is elaborated in **APPENDIX-I**.

2. Executive Summary (LSA)

2.1 Drive test details

This report covers the findings of the IDT undertaken in North East License Service Area (LSA) during the month of March 2025 under the supervision of TRAI Regional Office (RO), Kolkata. Details of route/area covered during the IDT is as given below:

Sl. No	Drive test route	Type of route	Distance covered (KMs)/ Locations	From date	To date
1	Aizawl city & Kolasib district	City	145.5	20-Mar-2025	21-Mar-2025
2	Aizawl city & Kolasib district	Hotspot	5 Locations	19-Mar-2025	21-Mar-2025
3	Aizawl	Walk Test	0.9	20-Mar-2025	21-Mar-2025

Table-1: Drive test summary.

2.2 Drive test routes

The map provides overview of drive test routes indicating city drive, hotspots and walk test as per the legends shown on the map.




Figure-1: Drive test routes.

2.3 Summary of areas covered

a) City- Kolasib, North Thingdawl, Sethawn, Kawnpui, Durtlang, Khatla South, Tlangnuam, Sihphir, Bawngkawn, Sairang, MG Road.

b) Hotspot

1. National Institute of Technology - Mizoram
2. Civil Hospital, Aizawl
3. Office of the Deputy Commissioner - Kolasib District
4. Jawahar Navodaya Vidyalaya – Kolasib, Thingdawl
5. Kawnpui Post Office

c) Walk Test

1. Aizawl Airport
2. Aizawl High Court

2.4 Telecom service providers detected frequency bands


Technologies covered during the IDT and frequency bands in use are summarised in below table.

S.No.	Name of TSP	Technology	Frequency Bands (In MHz)
1	Bharti Airtel Ltd.	2G	900
2	Bharti Airtel Ltd.	4G	900,1800,2100,2300
3	Bharti Airtel Ltd.	5G	3500
4	BSNL	2G	900
5	BSNL	3G	2100
6	BSNL	4G	700,2100
7	Reliance JIO Infocomm Ltd.	4G	850,1800,2300
8	Reliance JIO Infocomm Ltd.	5G	700,3500
9	Vodafone Idea Ltd.	2G	1800
10	Vodafone Idea Ltd.	3G	2100
11	Vodafone Idea Ltd.	4G	1800,2500

Table-2: Telecom service provider (TSP) covered in IDT.

2.5 Performance against key QoS parameters

CSSR: Call setup success rate (in %), CST: Call setup time (in milli seconds), DCR: Drop call rate (in %) & MOS: Mean Opinion Score.



Summary-Voice Service

Call Setup Success Rate: Airtel, BSNL, RJIL and VIL have call setup success rate of 94.41%, 69.23%, 100.00% and 81.71% respectively in Auto-selection mode (5G/4G/3G/2G).

Call Setup Time: Airtel, BSNL, RJIL and VIL have call setup time of 3.76, 2.49, 1.02 & 2.46 seconds respectively in Auto-selection mode (5G/4G/3G/2G).

Drop Call Rate: Airtel, BSNL, RJIL and VIL have drop call rate of 0.35%, 2.78%, 0.32% & 4.20% respectively in Auto-selection mode (5G/4G/3G/2G).

Call Silence/Mute Rate: Airtel, BSNL, RJIL and VIL have silence call rate 3.18%, 1.53%, 4.76% and 6.94% respectively in packet switched network (4G/5G).

Mean Opinion Score (MOS): Airtel, BSNL, RJIL and VIL have average MOS Score of 3.97, 3.37, 3.79 & 4.49 respectively.

Summary-Data Service

Data Download performance (Overall):

Average download speed of Airtel (5G/4G/2G) is 84.23 Mbps, BSNL (4G/3G/2G) is 5.87 Mbps, RJIL (5G/4G) is 84.89 Mbps and VIL (4G/3G/2G) is 21.75 Mbps.

Data Upload performance (Overall):

Average upload speed of Airtel (5G/4G/2G) is 15.36 Mbps, BSNL (4G/3G/2G) is 3.49 Mbps, RJIL (5G/4G) is 6.73 Mbps and VIL (4G/3G/2G) is 5.95 Mbps.

Data performance - Hotspots (in Mbps):

Airtel- 4G D/L: 22.89	4G U/L: 8.68
5G D/L: 149.69	5G U/L: 76.89
BSNL- 4G D/L: 8.54	4G U/L: 6.39
RJIL- 4G D/L: 21.63	4G U/L: 4.80
5G D/L: 265.81	5G U/L: 31.02
VIL- 4G D/L: 30.92	4G U/L: 7.55

Note- "D/L" Download speed, "U/L" Upload speed

QoS Performance Analysis- North East LSA

3. QoS performance analysis- LSA level

3.1 Overview

This section provides summary of overall QoS performance of the telecom service provider's network in the LSA by aggregating the results of drive tests conducted in the LSA during the month of March-2025 covering city, hotspot and walk test. (refer table 1)

3.2 Voice performance

(a) Voice Call Performance in 3G/2G network mode only: 3G/2G network mode testing has been done to reflect experience for respective users as they have only 3G/2G compatible handsets.

Parameters	Service Provider		
	3G/2G network mode only		
	AIRTEL	BSNL	VIL
Call Attempts	224	258	255
Call Setup Success Rate %	96.88	87.98	84.31
Drop Call Rate %	0.46	13.66	7.44
Call Setup Time-Average (Second)	5.99	3.40	4.13
Handover Success Rate %	99.69	93.24	99.73

Table-3: Summary of voice call performance in 3G/2G network mode only.




Figure-2: Call setup success rate and drop call rate performance.

Number of unique cell id's covered in Voice test- Technology wise			
Technology	Service Provider		
	3G/2G network mode only		
	AIRTEL	BSNL	VIL
3G	NA	27	6
2G	186	109	162

Table-4: Technology wise number of network cell id's latched during drive test.

Note-

- RJIL does not have 3G/2G network.
- NA- Service provider doesn't provide services in respective technology.

(b) Voice Call Performance in auto network selection mode (5G/4G/3G/2G)

Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempts	307	364	308	350
Call Setup Success Rate %	94.14	69.23	100.00	81.71
Drop Call Rate %	0.35	2.78	0.32	4.20
Call Setup Time-Average (Second)	3.76	2.49	1.02	2.46
Handover Success Rate %	99.91	99.52	99.89	99.81

Table-5: Summary of voice call performance in network auto-selection mode.




Figure-3: Performance for call setup success rate and drop call rate.

Parameter	Service Provider			
	Mobile-to-Mobile (5G/4G - Open Mode)			
	AIRTEL	BSNL	RJIL	VIL
Call Established (within service provider Network)	220	262	231	245
Number of silence call for >4 Sec	7	4	11	17
Silence Call Rate %	3.18	1.53	4.76	6.94
Number of silence instances for >4 Sec	10	5	17	23
Number of silence instances for >3 Sec	14	8	22	28
Number of silence instances for >2 sec	19	13	52	54
RTP Jitter (4G & 5G) in ms	3.95	13.26	9.15	6.24
Packet loss Rate Downlink %	1.33	2.96	0.65	2.17
Packet loss Rate Uplink %	1.21	1.64	2.29	1.93

Table-6: Summary of silence instances & packet loss rate for mobile to mobile call.

Number of unique cell id's covered in Voice test- Technology wise				
Technology	Service Provider			
	Auto Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
5G	0	NA	118	NA
4G	698	141	603	202
3G	NA	18	NA	2
2G	8	38	NA	59

Table-7: Technology wise number of network cell id's latched during drive test.

Note-

- NA- Service provider doesn't provide services on respective technology.

(c) Mean Opinion Score (MOS) performance for speech quality:

Mean opinion score indicates quality of speech observed during the drive test across different technologies. This parameter has been calculated for mobile-to-mobile calls made within same operator network in auto mode (5G/4G/3G/2G). As per ITU-T Recommendation P.863.1, MOS score values means: 5-Excellent, 4-Good, 3-Fair, 2-Poor, 1-Bad.

Speech Quality (MOS) distribution	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
Total Number of MOS Samples for calls in table-6	1847	1589	1917	1573
Speech Quality (Average MOS Score)	3.97	3.37	3.79	4.49
Number of samples with MOS ≥ 4 to < 5 (Excellent)	1482	690	1278	1391
Number of samples with MOS ≥ 3 to < 4 (Good)	287	385	426	103
Number of samples with MOS ≥ 2 to < 3 (Fair)	43	332	126	33
Number of samples with MOS ≥ 1 to < 2 (Poor)	35	182	87	46
%age of samples with MOS ≥ 4 to < 5 (Excellent)	80.24%	43.42%	66.67%	88.43%
%age of samples with MOS ≥ 3 to < 4 (Good)	15.54%	24.23%	22.22%	6.55%
%age of samples with MOS ≥ 2 to < 3 (Fair)	2.33%	20.89%	6.57%	2.10%
%age of samples with MOS ≥ 1 to < 2 (Poor)	1.89%	11.45%	4.54%	2.92%

Table-8: Summary of speech quality (MOS) samples.




Figure- 4: Distribution of samples in MOS score range.

3.3 Data performance

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Parameters		Service Provider			
		Auto-selection mode (5G/4G/3G/2G)			
		AIRTEL	BSNL	RJIL	VIL
Download Throughput (Mbits/s)	Average	84.23	5.87	84.89	21.75
	80th Percentile	137.36	9.06	124.32	38.78
	20th Percentile	14.09	1.83	4.02	5.31
Upload Throughput (Mbits/s)	Average	15.36	3.49	6.73	5.95
	80th Percentile	25.32	5.81	7.66	9.58
	20th Percentile	1.71	1.55	1.14	1.33
Latency (ms)	50th Percentile	29.50	24.20	27.10	53.50

Table-9: Summary of data performance in network auto-selection mode.




Figure- 5: Download and upload throughput.

Number of unique cell id's covered in Data test- Technology wise				
Technology	Service Provider			
	Auto-selection mode 5G/4G/3G/2G			
	AIRTEL	BSNL	RJIL	VIL
5G	0	NA	188	NA
4G	697	141	443	208
3G	NA	20	NA	6
2G	1	34	NA	65

Table-10: Technology wise number of network cell id's latched during drive test.

Note-

- NA- Service provider doesn't provide services in respective technology.

Detailed QoS Performance Analysis

4. Detailed QoS performance analysis

4.1 Overview

This section covers analysis on performance of various categories of drives like city, hotspots and walk tests for all telecom service providers, the results of drive tests conducted are shown individually for respective areas/locations.

4.2 City

Drive test has been conducted on 20th March 2025 and 21st March 2025 in Aizawl city & Kolasib district. (refer table-1)

4.2.1 Drive test route




Figure- 6: Drive test routes.

4.2.2 Areas covered

Kolasib, North Thingdawl, Sethawn, Kawnpui, Durtlang, Khatla South, Tlangnuam, Sihphir, Bawngkawn, Sairang, MG Road.

4.2.3 Voice performance

(a) Voice Call Performance in 3G/2G network mode only: 3G/2G network mode testing has been done to reflect experience for respective users as they have only 3G/2G compatible handsets.

Parameters	Service Provider		
	3G/2G network mode only		
	AIRTEL	BSNL	VIL
Call Attempts	224	258	255
Call Setup Success Rate %	96.88	87.98	84.31
Drop Call Rate %	0.46	13.66	7.44
Call Setup Time-Average (Second)	5.99	3.40	4.13
Handover Success Rate %	99.69	93.24	99.73

Table-11: Summary of voice call performance in 3G/2G network mode only.




Figure-7: Performance for call setup success rate.




Figure-8: Performance for drop call rate.

(b) Network Technology: This section represents time spent on various network technologies.

Technology	Service Provider		
	AIRTEL	BSNL	VIL
3G	NA	20.15%	15.91%
2G	99.90%	78.36%	83.75%
Limited Service	0.10%	1.49%	0.34%

Table-12: Time spent on technology during drive test 3G/2G network mode only.




Figure-9: Serving technology plots 3G/2G network mode – AIRTEL.




Figure-10: Serving technology plots 3G/2G network mode – BSNL.




Figure-11: Serving technology plots 3G/2G network mode –VIL.

(c) Network Signal Strength distribution: The following chart represents signal strength distribution for 3G/2G network mode only. (refer figure-31, 32 & 33 for map view)




Figure-12: Signal strength distribution 3G/2G network mode only.

Observations:

- Airtel has 12% of samples falling in the excellent signal strength category.
- BSNL has 25% of samples falling in the excellent signal strength category.
- VIL has 13% of samples falling in the excellent signal strength category.

(d)Voice Call Performance in auto network selection mode (5G/4G/3G/2G)

Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempts	236	287	238	273
Call Setup Success Rate %	92.80	69.69	100.00	80.95
Drop Call Rate %	0.46	3.50	0.42	4.07
Call Setup Time Average (Second)	4.15	2.45	1.08	2.46
Handover Success Rate %	99.91	99.49	99.93	99.80

Table-13: Summary of voice call performance in network auto-selection mode.




Figure-13: Performance for call setup success rate.




Figure-14: Performance for drop call rate.

Parameter	Service Provider			
	Mobile-to-Mobile (5G/4G - Open Mode)			
	AIRTEL	BSNL	RJIL	VIL
Call Established (within service provider Network)	220	262	231	245
Number of silence call for >4 Sec	7	4	11	17
Silence Call Rate %	3.18	1.53	4.76	6.94
Number of silence instances for >4 Sec	10	5	17	23
Number of silence instances for >3 Sec	14	8	22	28
Number of silence instances for >2 sec	19	13	52	54
RTP Jitter (4G & 5G) in ms	3.95	13.26	9.15	6.24
Packet loss Rate Downlink %	1.33	2.96	0.65	2.17
Packet loss Rate Uplink %	1.21	1.64	2.29	1.93

Table-14: Summary of silence instances & packet loss rate for mobile to mobile call.

(e) Mean Opinion Score (MOS) performance for speech quality:

Mean opinion score indicate quality of speech observed during the drive test across different technologies. This parameter has been calculated for mobile to mobile calls made within same operator network in auto mode (5G/4G/3G/2G). As per ITU-T Recommendation P.863.1, MOS score values means: 5-Excellent, 4-Good, 3-Fair, 2-Poor, 1-Bad.

Speech Quality (MOS) distribution	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
Total Number of MOS Samples for calls in table-14	1847	1589	1917	1573
Speech Quality (Average MOS Score)	3.97	3.37	3.79	4.49
Number of samples with MOS ≥ 4 to < 5 (Excellent)	1482	690	1278	1391
Number of samples with MOS ≥ 3 to < 4 (Good)	287	385	426	103
Number of samples with MOS ≥ 2 to < 3 (Fair)	43	332	126	33
Number of samples with MOS ≥ 1 to < 2 (Poor)	35	182	87	46
%age of samples with MOS ≥ 4 to < 5 (Excellent)	80.24%	43.42%	66.67%	88.43%
%age of samples with MOS ≥ 3 to < 4 (Good)	15.54%	24.23%	22.22%	6.55%
%age of samples with MOS ≥ 2 to < 3 (Fair)	2.33%	20.89%	6.57%	2.10%
%age of samples with MOS ≥ 1 to < 2 (Poor)	1.89%	11.45%	4.54%	2.92%

Table-15: Summary of speech quality (MOS) samples.




Figure-15: Distribution of samples in MOS score range.

(f) Network Technology: This section represents time spent on various network technologies.

Technology	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
5G	1.04%	NA	8.24%	NA
4G	94.90%	71.27%	91.76%	75.53%
3G	NA	7.73%	NA	0.28%
2G	2.89%	15.59%	NA	22.19%
Limited Service	1.17%	5.41%	0.00%	2.00%

Table-16: Time spent on technology during drive test.

Note-

- NA- Service provider doesn't provide services in respective technology.




Figure-16: Serving technology plots in auto-selection mode (5G/4G/3G/2G) –AIRTEL.




Figure-17: Serving technology plots in auto-selection mode (5G/4G/3G/2G) –BSNL.




Figure-18: Serving technology plots in auto-selection mode (5G/4G/3G/2G)- RJIL.




Figure-19: Serving technology plots in auto-selection mode (5G/4G/3G/2G) – VIL.

(g) Network Signal Strength distribution: The following chart provide signal strength distribution for auto-selection mode (5G/4G/3G/2G). (refer figure-34, 35, 36 & 37 for map view)




Figure-20: Signal strength distribution auto-selection mode 5G/4G/3G/2G.

Observations:

- Airtel has 16% of samples falling in the excellent signal strength category.
- BSNL has 12% of samples falling in the excellent signal strength category.
- RJIL has 18% of samples falling in the excellent signal strength category.
- VIL has 9% of samples falling in the excellent signal strength category.

4.2.4 Data performance

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Parameters		Service Provider			
		Auto-selection mode (5G/4G/3G/2G)			
		AIRTEL	BSNL	RJIL	VIL
Download Throughput (Mbits/s)	Average	91.67	5.47	90.98	23.74
	80th Percentile	143.36	8.00	134.38	39.93
	20th Percentile	17.75	1.74	4.81	8.80
Upload Throughput (Mbits/s)	Average	15.73	3.18	6.76	6.45
	80th Percentile	27.19	5.41	7.88	9.60
	20th Percentile	1.83	1.48	1.14	2.19
Latency (ms)	50th Percentile	29.20	24.75	28.30	49.48

Table-17: Summary of Data performance in network auto-selection mode.




Figure- 21: Download throughput.




Figure- 22: Upload throughput.

4.3 Hotspots

Hotspot testing has been done on 19th March 2025 and 21st March 2025. Five locations have been tested in the Aizawl city & Kolasib district.

4.3.1 Locations




Figure- 23: Hotspot locations

4.3.2 Hotspot covered

1. National Institute of Technology - Mizoram
2. Civil Hospital, Aizawl
3. Office of the Deputy Commissioner - Kolasib District
4. Jawahar Navodaya Vidyalaya – Kolasib, Thingdawl
5. Kawnpui Post Office

4.3.3 Voice performance

Overall Voice Performance				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	50	50	50	50
Call Setup Success Rate %	98.00	84.00	100.00	92.00
Drop Call Rate %	0.00	0.00	0.00	2.17
Call Setup Time-Average (Sec)	2.63	2.88	0.81	2.17

Table-18: Overall summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

National Institute of Technology - Mizoram				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Sec)	2.39	1.61	0.70	1.28

Table-19: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Civil Hospital, Aizawl				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Sec)	2.18	3.95	1.20	4.53

Table-20: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Office of the Deputy Commissioner - Kolasib District				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	80.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Sec)	2.24	4.16	0.62	1.18

Table-21: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Jawahar Navodaya Vidyalaya – Kolasib, Thingdawl				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	90.00	80.00	100.00	90.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Sec)	4.04	2.08	0.78	1.33

Table-22: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Kawnpui Post Office				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	40.00	100.00	90.00
Drop Call Rate %	0.00	0.00	0.00	11.11
Call Setup Time-Average (Sec)	2.42	1.82	0.73	2.25

Table-23: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

4.3.4 Data performance (Auto-selection mode 5G/4G/3G/2G)

Overall Data Performance				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	53.18	10.56	89.23	13.70
Download Throughput 80th Percentile (Mbit/s)	88.41	17.55	58.28	27.29
Download Throughput 20th Percentile (Mbit/s)	5.21	4.57	1.31	0.12
Download Session Setup Success Rate %	100.00	88.00	76.00	92.00
Upload Throughput Average (Mbits/s)	23.56	6.67	10.77	2.34
Upload Throughput 80th Percentile (Mbit/s)	27.23	8.54	23.50	3.92
Upload Throughput 20th Percentile (Mbit/s)	1.61	3.97	1.60	0.09
Upload Session Setup Success Rate %	100.00	88.00	88.00	96.00
Web Browsing Delay (Second)	4.96	4.82	5.55	6.72
Youtube Initial Buffer Delay (Second)	1.92	1.58	2.06	3.16
Latency (ms)-50th Percentile	29.50	23.50	25.50	61.50
Jitter (ms)	27.64	3.77	85.70	34.53
Packet Loss Rate%	1.90	0.68	14.08	41.10
Packet Loss Rate- 90th percentile	5.42	1.98	30.84	100.00

Table-24: Overall Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

National Institute of Technology - Mizoram				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	15.31	6.29	1.13	37.94
Download Session Setup Success Rate %	100.00	100.00	80.00	100.00
Upload Throughput Average (Mbits/s)	2.80	7.65	4.07	9.07
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	5.38	4.94	8.58	5.76
Youtube Initial Buffer Delay (Second)	2.09	0.92	4.02	0.96
Latency (ms)-50th Percentile	33.20	20.05	39.30	48.40
Jitter (ms)	26.50	2.13	54.42	3.16
Packet Loss Rate%	0.80	0.30	20.10	0.30

Table-25: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Civil Hospital, Aizawl				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	18.11	15.42	1.05	0.08
Download Session Setup Success Rate %	100.00	100.00	40.00	100.00
Upload Throughput Average (Mbits/s)	5.12	5.76	1.51	0.08
Upload Session Setup Success Rate %	100.00	100.00	40.00	100.00
Web Browsing Delay (Second)	4.50	4.80	6.21	-
Youtube Initial Buffer Delay (Second)	1.05	1.21	4.22	-
Latency (ms)-50th Percentile	31.90	20.15	58.00	221.00
Jitter (ms)	5.93	3.42	310.12	93.12
Packet Loss Rate%	0.20	0.00	38.00	100.00

Table-26: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note-

- “-”All Web Browsing and YouTube test were failed.

Office of the Deputy Commissioner - Kolasib District				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	105.58	19.27	318.97	24.13
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	104.30	7.12	36.87	1.29
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	3.43	4.21	3.84	5.73
Youtube Initial Buffer Delay (Second)	0.64	0.90	0.85	3.48
Latency (ms)-50th Percentile	21.75	21.05	15.55	57.50
Jitter (ms)	3.53	2.32	1.65	7.17
Packet Loss Rate%	0.00	0.00	0.00	1.30

Table-27: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Jawahar Navodaya Vidyalaya – Kolasib, Thingdawl				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	0.62	4.22	12.35	0.80
Download Session Setup Success Rate %	100.00	60.00	60.00	100.00
Upload Throughput Average (Mbits/s)	0.96	10.96	4.28	0.68
Upload Session Setup Success Rate %	100.00	60.00	100.00	100.00
Web Browsing Delay (Second)	16.83	4.88	4.68	9.57
Youtube Initial Buffer Delay (Second)	5.86	3.40	1.50	5.04
Latency (ms)-50th Percentile	38.30	44.98	21.35	54.00
Jitter (ms)	99.03	3.37	42.93	7.37
Packet Loss Rate%	8.50	0.00	11.10	3.90

Table-28: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Kawnpui Post Office				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	126.30	3.68	11.36	0.15
Download Session Setup Success Rate %	100.00	80.00	100.00	60.00
Upload Throughput Average (Mbits/s)	4.59	2.81	1.57	0.13
Upload Session Setup Success Rate %	100.00	80.00	100.00	80.00
Web Browsing Delay (Second)	5.74	5.37	5.41	-
Youtube Initial Buffer Delay (Second)	3.18	1.43	1.77	-
Latency (ms)-50th Percentile	25.33	33.00	24.05	245.50
Jitter (ms)	4.53	7.72	20.43	61.98
Packet Loss Rate%	0.00	3.10	1.20	100.00

Table-29: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note-

- “-”All Web Browsing and YouTube test were failed.

4.3.5 Data performance (5G Only & 4G Only Download & Upload Speed)

Overall Data Performance					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	149.69	-	265.81	-
	Upload Throughput Average (Mbits/s)	76.89	-	31.02	-
4G	Download Throughput Average (Mbits/s)	22.89	8.54	21.63	30.92
	Upload Throughput Average (Mbits/s)	8.68	6.39	4.80	7.55

Table-30: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

National Institute of Technology - Mizoram					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	-	-	-	-
	Upload Throughput Average (Mbits/s)	-	-	-	-
4G	Download Throughput Average (Mbits/s)	38.78	9.40	0.79	44.59
	Upload Throughput Average (Mbits/s)	3.64	7.50	1.20	9.55

Table-31: Summary of data download & upload speed 5G only & 4G only.

Note- “-”Respective technology was not observed during the test.

Civil Hospital, Aizawl					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	-	-	-	-
	Upload Throughput Average (Mbits/s)	-	-	1.76	-
4G	Download Throughput Average (Mbits/s)	14.68	10.91	2.65	23.68
	Upload Throughput Average (Mbits/s)	8.30	5	1.17	9.62

Table-32: Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

Office of the Deputy Commissioner - Kolasib District					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	105.58	-	318.97	-
	Upload Throughput Average (Mbits/s)	104.30	-	36.87	-
4G	Download Throughput Average (Mbits/s)	31.92	8.03	69.02	42.00
	Upload Throughput Average (Mbits/s)	21.87	8.28	18.10	9.43

Table-33: Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

Jawahar Navodaya Vidyalaya – Kolasib, Thingdawl					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	-	-	-	-
	Upload Throughput Average (Mbits/s)	-	-	-	-
4G	Download Throughput Average (Mbits/s)	1.41	4.02	28.51	13.42
	Upload Throughput Average (Mbits/s)	0.89	4.37	1.97	1.59

Table-34: Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

Kawnpui Post Office					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	259.94	-	-	-
	Upload Throughput Average (Mbits/s)	8.35	-	-	-
4G	Download Throughput Average (Mbits/s)	23.36	-	8.56	-
	Upload Throughput Average (Mbits/s)	8.70	-	1.56	-

Table-35: Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

4.4 Walk Test

Walk Test has been conducted on 20th March 2025 and 21st March 2025. Two locations have been tested in the city.

4.4.1 Locations




Figure-24: Walk Test location.

4.4.2 Walk Test Covered

1. Aizawl Airport
2. Aizawl High Court

4.4.3 Voice Performance

i) Aizawl Airport

(a) Voice Call Performance in auto network selection mode (5G/4G/3G/2G)

Aizawl Airport				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	11	16	10	16
Call Setup Success Rate %	100.00	0.00	100.00	56.25
Drop Call Rate %	0.00	-	0.00	22.22
Call Setup Time-Average (Second)	2.52	-	0.68	1.27
Handover Success Rate %	100.00	-	100.00	100.00

Table-36: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Note- All calls in BSNL were blocked due to call setup timeout.




Figure- 25: Performance for call setup success rate and drop call rate.

(b) Network Technology: This section represents time spent on various network technologies.

Aizawl Airport				
Technology	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
5G	0.00%	NA	0.00%	NA
4G	100.00%	14.87%	100.00%	56.19%
3G	NA	4.27%	NA	0.00%
2G	0.00%	15.03%	NA	27.83%
Limited service	0.00%	65.82%	0.00%	15.98%

Table-37: Time spent on technology during Walk test.

Note-

- NA- Service provider doesn't provide services on respective technology.

(c) Network Signal Strength distribution: The following chart provide signal strength distribution for auto-selection mode (5G/4G/3G/2G).




Figure-26: Signal strength distribution auto-selection mode 5G/4G/3G/2G.

ii) Aizawl High Court

(a) Voice Call Performance in auto network selection mode (5G/4G/3G/2G).

Aizawl High Court				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	11	10	11
Call Setup Success Rate %	100.00	90.91	100.00	90.91
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	2.52	1.79	0.68	1.27
Handover Success Rate %	100.00	100.00	98.82	100.00

Table-38: Summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).




Figure- 27: Performance for call setup success rate and drop call rate.

(b) Network Technology: This section represents time spent on various network technologies.

Aizawl High Court				
Technology	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
5G	0.62%	NA	10.99%	NA
4G	99.38%	100.00%	89.01%	100.00%
3G	NA	0.00%	NA	0.00%
2G	0.00%	0.00%	NA	0.00%
Limited service	0.00%	0.00%	0.00%	0.00%

Table-39: Time spent on technology during Walk test.

Note-

- NA- Service provider doesn't provide services on respective technology.

(c) Network Signal Strength distribution: The following chart provides signal strength distribution for auto-selection mode (5G/4G/3G/2G).




Figure-28: Signal strength distribution auto-selection mode 5G/4G/3G/2G.

4.4.4 Data Performance

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Aizawl Airport				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	36.06	-	3.47	2.53
Download Throughput 80th Percentile	68.91	-	5.69	3.24
Download Throughput 20th Percentile	14.16	-	1.07	1.55
Download Session Setup Success Rate %	100.00	0.00	100.00	75.00
Upload Throughput Average (Mbits/s)	4.02	-	1.24	1.84
Upload Throughput 80th Percentile	5.32	-	1.22	2.73
Upload Throughput 20th Percentile	2.32	-	0.78	1.23
Upload Session Setup Success Rate %	100.00	0.00	100.00	66.67
Latency (ms) - 50th Percentile	31.40	-	31.80	136.00

Table-40: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Note-

- “-”All download, upload and latency tests were failed.




Figure- 29: Download and Upload throughput.

Aizawl High Court				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	24.67	4.44	35.30	10.46
Download Throughput 80th Percentile	38.22	7.84	57.50	12.84
Download Throughput 20th Percentile	4.31	0.98	7.80	3.07
Download Session Setup Success Rate %	100.00	100.00	92.31	100.00
Upload Throughput Average (Mbits/s)	3.35	2.82	4.53	5.55
Upload Throughput 80th Percentile	5.53	3.14	6.91	9.58
Upload Throughput 20th Percentile	1.48	1.85	2.39	1.89
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Latency (ms) - 50th Percentile	38.78	24.73	23.53	50.50

Table-41: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).




Figure- 30: Download and Upload throughput.

5. Voice & Data Key findings

5.1 Overall Voice

1. Call Setup Success Rate:

- a) Airtel, BSNL and VIL have 96.88%, 87.98% and 84.31% call setup success rate respectively in 3G/2G network mode. (refer table-3)
- b) Airtel, BSNL, RJIL and VIL have 94.14%, 69.23%, 100.00% and 81.71% call setup success rate respectively in Auto-selection mode (5G/4G/3G/2G). (refer table-5)

2. Call Setup Time:

- a) Airtel, BSNL and VIL call setup time is 5.99, 3.40 & 4.13 seconds respectively in 3G/2G network mode. (refer table-3)
- b) Airtel, BSNL, RJIL & VIL call setup time is 3.76, 2.49, 1.02 & 2.46 seconds respectively in Auto-selection mode (5G/4G/3G/2G). (refer table-5)

3. Drop Call Rate:

- a) Airtel, BSNL and VIL drop call rate is 0.46%, 13.66% & 7.44% respectively in 3G/2G network mode. (refer table-3)
- b) Airtel, BSNL, RJIL and VIL drop call rate is 0.35%, 2.78% 0.32% & 4.20% respectively in Auto-selection mode (5G/4G/3G/2G). (refer table-5)

- 4. **Call Silence/Mute Rate:** In packet switched network (4G/5G), VIL, RJIL, Airtel and BSNL have 6.94%, 4.76%, 3.18% & 1.53% silence call rate respectively. Further BSNL has higher RTP packet loss rate in downlink (2.96%) compared to VIL (2.17%), Airtel (1.33%) and RJIL (0.65%). In uplink the RTP packet loss rate is higher for RJIL (2.29%) compared to VIL (1.93%), BSNL (1.64%) and Airtel (1.21%). (refer table-6)

5.2 Overall Data

1. Data download and upload performance (Overall i.e. LSA):

- a) Airtel, BSNL, RJIL and VIL average download speeds are 84.23 Mbps, 5.87 Mbps, 84.89 Mbps & 21.75 Mbps respectively. (refer table-9)
- b) Airtel, BSNL, RJIL and VIL average upload speeds are 15.36 Mbps, 3.49 Mbps, 6.73 Mbps & 5.95 Mbps respectively. (refer table-9)

2. Data download and upload performance (static i.e. while stationary):

- a) Airtel, BSNL, RJIL and VIL average download speeds are 53.18 Mbps, 10.56 Mbps, 89.23 Mbps & 13.70 Mbps respectively. (refer table-24)
- b) Airtel, BSNL, RJIL and VIL average upload speeds are 23.56 Mbps, 6.67 Mbps, 10.77 Mbps & 2.34 Mbps respectively. (refer table-24)

3. Data session setup success rate (static i.e. while stationary):

- a) Airtel, BSNL, RJIL and VIL have 100.00%, 88.00%, 76.00% and 92.00% download session setup success rate respectively. (refer table-24)
- b) Airtel, BSNL, RJIL and VIL have 100.00%, 88.00%, 88.00% and 96.00% upload session setup success rate respectively. (refer table-24)

5.3 Operator wise Key Findings

1. Airtel:

Voice

- 96.88% call setup success rate and 0.46% drop call rate have been observed for 3G/2G network mode for LSA & City Drive. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-3 & 11)
- 94.14% call setup success rate and 0.35% drop call rate have been observed for auto-selection mode (5G/4G/3G/2G) for LSA. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-5)
- 92.80% call setup success rate and 0.46% drop call rate have been observed for auto-selection mode (5G/4G/3G/2G) for City Drive. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-13)
- 98.00% call setup success rate and 0.00% drop call rate have been observed for auto-selection mode (5G/4G/3G/2G) for hotspot locations. Performance is meeting the benchmark of 98.00% & 2.00% respectively. (refer table-18)
- 100% call setup success rate and 0.00% drop call rate have been observed for auto-selection mode (5G/4G/3G/2G) for both walk test locations. Performance is well within the benchmark of 98.00% & 2.00% for call setup success rate and drop call rate respectively. (refer table-36 & 38)

Data

- Airtel has average download throughput of 84.23 Mbps and average upload throughput of 15.36 Mbps across measured routes for LSA. (refer table-9)
- Airtel has average download throughput of 91.67 Mbps and average upload throughput of 15.73 Mbps across the measured routes during the city drive. (refer table -17)
- National Institute of Technology - Mizoram, Civil Hospital, Aizawl and Jawahar Navodaya Vidyalaya – Kolasib, Thingdawl have less download speed (less than 100 Mbps) out of total 5 Hotspots for auto-selection mode (5G/4G/3G/2G). (refer table-25, 26 and 28)
- National Institute of Technology - Mizoram, Civil Hospital, Aizawl, Jawahar Navodaya Vidyalaya – Kolasib, Thingdawl and Kawnpui Post Office have less

upload speed (less than 20 Mbps) out of total 5 Hotspots for auto-selection mode (5G/4G/3G/2G). (refer table-25, 26, 28 and 29)

- Aizawl Airport & Aizawl High court both walk test locations have less download speed (less than 100 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-40 & 41)
- Aizawl Airport & Aizawl High Court both walk test locations have less upload speed (less than 20 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-40 & 41)

2. BSNL:

Voice

- 87.98% call setup success rate and 13.66% drop call rate have been observed in 3G/2G network mode for LSA & city drive. Performance is not meeting the benchmark of 98.00% & 2.00% for call setup success rate and drop call rate respectively. (refer table-3 & 11)
- 69.23% call setup success rate and 2.78% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G). Performance is not meeting the benchmark of 98.00% & 2.00% for call setup success rate and drop call rate respectively for LSA. (refer table-5)
- 69.69% call setup success rate and 3.50% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. Performance is not meeting the benchmark of 98.00% & 2.00% for call setup success rate and drop call rate. (refer table-13)
- 84.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for overall hotspot locations. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-18)
- 0.00% & 90.91% call setup success rate has been observed for auto-selection mode (5G/4G/3G/2G) at Aizawl Airport & Aizawl High Court Walk test locations respectively. Performance is not meeting the benchmark of 98.00% for call setup success rate. (refer table-36 & 38)

Data

- BSNL has 5.87 Mbps average download throughput & 3.49 Mbps average upload throughput across measured routes for LSA. (refer table-9)
- BSNL has 5.47 Mbps average download throughput & 3.18 Mbps average upload throughput across measured routes for city drive. (refer table-17)
- National Institute of Technology - Mizoram, Jawahar Navodaya Vidyalaya – Kolasib, Thingdawl and Kawnpui Post Office have less download speed (less

than 10 Mbps) out of total 5 Hotspots for auto-selection mode (5G/4G/3G/2G). (refer table-25, 28, 29)

- Aizawl Airport & Aizawl High Court both walk test locations have less download speed (less than 10 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-40 & 41)
- Aizawl Airport walk test location has less upload speed (less than 2 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-40)

3. RJIL:

Voice

- 100.00% call setup success rate and 0.32% drop call rate have been observed for the auto-selection mode for LSA. Performance is well within the benchmark of 98.00% & 2.00% for call setup success rate and drop call rate respectively. (refer table-5)
- 100.00% call setup success rate and 0.42% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. Performance is well within the benchmark of 98.00% & 2.00% for call setup success rate and drop call rate respectively. (refer table-13)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for overall hotspot locations. Performance is well within the benchmark of 98.00% & 2.00% for call setup success rate and drop call rate respectively. (refer table-18)
- 100% call setup success rate and 0.00% drop call rate have been observed for auto-selection mode (5G/4G/3G/2G) for both walk test locations. Performance is well within the benchmark of 98.00% & 2.00% for call setup success rate and drop call rate respectively. (refer table-36 & 38)

Data

- RJIL has 84.89 Mbps average download speed & 6.73 Mbps average upload speed across measured routes for LSA. (refer table-9)
- RJIL has 90.98 Mbps average download speed & 6.76 Mbps average upload speed across measured routes for city drive. (refer table-17)
- National Institute of Technology - Mizoram, Civil Hospital, Aizawl, Jawahar Navodaya Vidyalaya – Kolasib, Thingdawl and Kawnpui Post Office have less download speed (less than 100 Mbps) out of total 5 Hotspots for auto-selection mode (5G/4G/3G/2G). (refer table-25, 26, 28 and 29)
- National Institute of Technology - Mizoram, Civil Hospital, Aizawl, Jawahar Navodaya Vidyalaya – Kolasib, Thingdawl and Kawnpui Post Office have less

upload speed (less than 20 Mbps) out of total 5 Hotspots for auto-selection mode (5G/4G/3G/2G). (refer table-25, 26, 28 and 29)

- Aizawl Airport & Aizawl High court both walk test locations have less download speed (less than 100 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-40 & 41)
- Aizawl Airport & Aizawl High Court both walk test locations have less upload speed (less than 20 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-40 & 41)

4. VIL:

Voice

- 84.31% call setup success rate and 7.44% drop call rate have been observed in 3G/2G network mode for LSA & city drive. Performance is not meeting the benchmark of 98.00% & 2.00% for call setup success rate and drop call rate respectively. (refer table-3 & 11)
- 81.71% call setup success rate and 4.20% drop call rate have been observed for auto-selection mode (5G/4G/3G/2G) for LSA. Performance is not meeting the benchmark of 98.00% & 2.00% for call setup success rate and drop call rate respectively. (refer table-5)
- 80.95% call setup success rate and 4.07% drop call rate have been observed for auto-selection mode (5G/4G/3G/2G) for city drive. Performance is not meeting the benchmark of 98.00% & 2.00% for call setup success rate and drop call rate respectively. (refer table-13)
- 92.00% call setup success rate and 2.17% drop call rate have been observed for auto-selection mode (5G/4G/3G/2G) for overall hotspot locations. Performance is not meeting the benchmark of 98.00% & 2.00% for call setup success rate and drop call rate respectively. (refer table-18)
- 56.25% & 90.91% call setup success rate and 22.22% & 0.00 drop call rate have been observed for auto-selection mode (5G/4G/3G/2G) at Aizawl Airport & Aizawl High Court Walk test locations respectively. Performance is not meeting the benchmark of 98.00% at both location for call setup success rate & 2.00% at Aizawl Airport for drop call rate. (refer table-36 & 38)

Data

- VIL has 21.75 Mbps average download speed & 5.95 Mbps average upload speed across measured routes for LSA. (refer table-9)
- VIL has 23.74 Mbps average download speed & 6.45 Mbps average upload speed across measured routes for city drive. (refer table-17)
- Civil Hospital, Aizawl, Jawahar Navodaya Vidyalaya – Kolasib, Thingdawl, Kawnpui Post Office have less download speed (less than 10 Mbps) out of total 5 Hotspots for auto-selection mode (5G/4G/3G/2G). (refer table-26, 28, 29)

- Civil Hospital, Aizawl, Office of the Deputy Commissioner - Kolasib District, Jawahar Navodaya Vidyalaya – Kolasib, Thingdawl and Kawnpui Post Office have less upload speed (less than 2 Mbps) out of total 5 Hotspots for auto-selection mode (5G/4G/3G/2G). (refer table-26, 27, 28 and 29)
- Aizawl Airport Walk test location has less download speed (less than 10 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-40)
- Aizawl Airport Walk test location have less upload speed (less than 2 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table-40)

6. Annexure

6.1 Route wise coverage map

6.1.1 City




Figure-31: Signal strength 3G/2G network mode – AIRTEL.




Figure-32: Signal strength 3G/2G network mode – BSNL.




Figure-33: Signal strength 3G/2G network mode – VIL.




Figure-34: Signal strength auto-selection mode 5G/4G/3G/2G – AIRTEL.




Figure-35: Signal strength auto-selection mode 5G/4G/3G/2G – BSNL.




Figure-36: Signal strength auto-selection mode 5G/4G/3G/2G – RJIL.




Figure-37: Signal strength auto-selection mode 5G/4G/3G/2G – VIL.

7. Appendix

The details of the setup used for conducting the drive test and the network or performance parameters captured under different conditions may be seen at Appendix-I. The calculation method of each QoS parameter is given in Appendix-II of the report. The summary of key equipment used in technical setup is as under

- **Device-1:** OnePlus Nord CE3 for 3G/2G CAT-15 Smartphone.
- **Device-2:** Samsung Galaxy S23 for 5G/4G/3G/2G CAT-20 Smartphone
- **Drive test Software:** Azenqos Engineering capable Applications to capture actual user experience.

7.1 Appendix-I

7.1.1 Drive test setup

Voice Call		
Call details	Technology	Detail
Call Setup Timeout	• 3G/2G auto mode- switch Call • 5G/4G/3G/2G auto mode- switch Call • 5G/4G MOS Call	30 Sec
Call Duration		120 Sec
Wait/Guard Time		15 Sec

Table-42: Voice test detail

Note-

- There is 15 sec wait time after locking and before starting first call in 3G/2G call.
- 10 calls to be made at each Hotspot location.
- Minimum 10 Calls to be made during the walk test. Call count will be increased based on walk test distance.
- Speech quality (MOS) has been measured only in city drive & highway by making Mobile to Mobile call.
- 180 Sec calls were made only in highway & railway route drive.
- 5G/4G/3G/2G auto mode MOS call were made in BSNL as BSNL don't have VoLTE & VoNR network availability.

Data Test		
Test Type	Technology	Detail
HTTP/FTP Download	5G/4G/3G/2G Auto Mode	500 MB File- 30 Sec Timeout, (Multithread 3- TCP Connection at a time)
HTTP/FTP Upload		250 MB File- 30 Sec Timeout, (Multithread 3- TCP Connection at a time)
YouTube Streaming		20 Sec Video & 25 sec Timeout (Only at Hotspot)

Web Browsing		3 popular websites (www.amazon.in , www.flipkart.com , www.paytm.com) 20 sec timeout (only at Hotspot)
Latency		25 count- Dynamic 1000 count- Hotspot Payload- 512 bytes in all drive

Table-43: Data test detail

Note-

- 5 Data iteration to be done at each hotspot location.
- Minimum 5 iteration to be made during the walk test. Iteration count will be increased based on walk test distance.
- Ping test to be performed only once at hotspot location.
- Youtube & Web browsing test to be performed at static location only.
- All values are taken up to two decimal places with round off.
- Download and upload testing has been done on FTP server for Airtel, BSNL & RJIL. (Airtel, BSNL & RJIL not provided HTTP server)
- VIL download and upload testing is done on HTTP Server.
- Download & Upload test performed at hotspot in 4G/3G/2G auto-selection also.




Figure-38: Number of handsets used in city & highway drive

MO: Mobile originating

MT: Mobile terminatng




Figure-39: Number of handsets used in railway/metro/walktest/hotspot & coastal area

7.1.2 Drive test Methodology

(a) Dynamic voice testing (on the move)




Figure-40: Voice test script for city/railway/metro/highway & coastal area

- 15 sec wait time is applied after locking Radio Access Technology (RAT) to 3G/2G and before starting first call in 3G/2G call.
- Speech quality (MOS) will be measured only City & Highway drive by making Mobile to Mobile calls.

(b) Hotspot voice testing



Figure-41: Voice test script for walktest/hotspot

- 10 calls to be made at each Hotspot location.
- Minimum 10 Calls to be made during the walk test. Call count will be increased based on walk test distance.

(c) Dynamic Data (internet) test




Figure-42: Data test script used in city/metro/railway/highway/walk test & coastal area

(d) Static Data(internet) testing




Figure-43: Data test script used at hotspot

- 5 Data iteration done at each hotspot location.
- Min. 5 iteration made during the walk test.
- Web browsing duration mentioned above is for one web site only.
- Only 1 ping iteration (with 1000 Count) done at hotspot location.
- Download & Upload test performed at hotspot in 4G/3G/2G auto-selection also.

7.2 Appendix-II

7.2.1 Network Performance Parameters for Voice calls

Parameter Name	Definition
Call Setup Success Rate	<p>(i) Call Setup Success Rate is defined as the ratio of Established Calls to Call Attempts. 'Established Calls' mean the following events have happened in call setup:</p> <ul style="list-style-type: none"> (a) Call attempt is made (b) The signaling channel is allocated (c) The call is routed to the outwards path of the terminating network (d) An alert signal is received by caller in the form of ring back tone, busy tone, or an announcement. <p>CSSR = (Total Call Established/ Total Call Attempt) *100</p> <p>As per QoS Regulation 2024 benchmark value is >=98%</p>
Drop Call Rate	<p>Drop call represents the service provider network's ability to maintain a call once it has been successfully established. This parameter shall include both incoming calls and outgoing calls which, once they have been established and have an assigned traffic channel/ bearer, are dropped, or interrupted before their normal completion by the user, the cause of the early termination being within the service provider's network</p> <p>Drop Call Rate = (Total Drop Call/Total Call Established) *100</p> <p>As per QoS Regulation 2024 benchmark value is <=2%</p>
Call Setup Time	<p>Time taken from call initiate to call alerting/ringing.</p> <p>Call Setup Time = T2- T1</p> <p>T2- Ringing (VoLTE/VoNR) & Alerting (for WCDMA & GSM), T1- Invite (VoLTE/VoNR) & CM Service Request (for WCDMA & GSM)</p>
Voice Quality (MOS)	<p>Voice quality in mobile networks is measured with algorithms based on ITU-T P.863 (POLQA). The grading for Voice quality has been given as:</p> <p>Excellent: MOS ≥ 4 and < 5 Good : MOS ≥ 3 and < 4 Fair : MOS ≥ 2 and < 3 Poor : MOS ≥ 1 and < 2</p>
Handover Success Rate	<p>Handover Success Rate = Count of successful handovers (All Technology Handover combined) / Total count of Handover Attempt (All Technology Handover combined) *100</p> <p>Handover type which are considered- 2G Inter & Intra cell, 3G Soft & IRAT, 4G Inter & Intra frequency & SRVCC, 5G Inter & Intra frequency & 5G to 4G handovers.</p>
Silence Call -	<p>A call which has ≥ 4 sec continuous RTP gap is considered as a Silence Call.</p> <p>Silence call rate = (count of silence call / Total calls established) *100</p> <p>If a call observes multiple silence count ≥ 4 sec in a particular established call it has been taken as one silent event.</p>

Jitter	<p>The inter arrival jitter is the difference in the relative transit time for two packets. The relative transit time is the difference between a packet's Real-time Transport Protocol (RTP) timestamp and the receiver's clock at the time of arrival, measured in the same units. If S_i is the RTP timestamp from packet i, and R_i is the time of arrival in RTP timestamps units for packet i, then for two packets i and j the inter-arrival jitter D can be expressed as:</p> $D(i,j) = (R_j - R_i) - (S_j - S_i)$ <p>The interarrival jitter is calculated continuously as each data packet i is received from source $SSRC_n$, using this difference D for that packet and the previous packet $i-1$ in order of arrival (not necessarily in sequence), according to the formula</p> $J(i) = J(i-1) + (D(i-1,i) - J(i-1))/16 \text{ or } 8$																																		
Downlink Packet Drop Rate	<p>Number of RTP (Real-time Transport Protocol) Packets lost divided by total RTP packet received (against each source_SSRC and sequence number) at call originating handset. This KPI is calculated from MOS call for packet call only (VoNR/VoLTE)</p>																																		
Uplink Packet Drop Rate	<p>Number of RTP (Real-time Transport Protocol) Packets lost divided by total RTP packet received (against each source_SSRC and sequence number) at call terminating handset. This KPI is calculated from MOS call for packet call only (VoNR/VoLTE).</p>																																		
Signal Strength	<p>Signal strength is the signal power level received by the wireless user.</p> <table><tr><th rowspan="2">Parameter Name</th><th rowspan="2">Technology</th><th colspan="4">Signal Strength (dBm)</th></tr><tr><th>Excellent</th><th>Good</th><th>Fair</th><th>Poor</th></tr><tr><td>Rx Level</td><td>GSM</td><td>0 to ≥ -65</td><td><-65 to ≥ -75</td><td><-75 to ≥ -85</td><td><-85 to min</td></tr><tr><td>RSCP</td><td>WCDMA</td><td>0 to ≥ -70</td><td><-70 to ≥ -80</td><td><-80 to ≥ -90</td><td><-90 to min</td></tr><tr><td>RSRP</td><td>LTE</td><td>0 to ≥ -80</td><td><-80 to ≥ -95</td><td><-95 to ≥ -110</td><td><-110 to min</td></tr><tr><td>SS_RSRP</td><td>NR</td><td>0 to ≥ -80</td><td><-80 to ≥ -95</td><td><-95 to ≥ -110</td><td><-110 to min</td></tr></table>	Parameter Name	Technology	Signal Strength (dBm)				Excellent	Good	Fair	Poor	Rx Level	GSM	0 to ≥ -65	<-65 to ≥ -75	<-75 to ≥ -85	<-85 to min	RSCP	WCDMA	0 to ≥ -70	<-70 to ≥ -80	<-80 to ≥ -90	<-90 to min	RSRP	LTE	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min	SS_RSRP	NR	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min
Parameter Name	Technology			Signal Strength (dBm)																															
		Excellent	Good	Fair	Poor																														
Rx Level	GSM	0 to ≥ -65	<-65 to ≥ -75	<-75 to ≥ -85	<-85 to min																														
RSCP	WCDMA	0 to ≥ -70	<-70 to ≥ -80	<-80 to ≥ -90	<-90 to min																														
RSRP	LTE	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min																														
SS_RSRP	NR	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min																														

Table-44: Network performance parameter and definition voice

7.2.2 Network Performance Parameters Data tests

Parameter Name	Definition
Download Speed (Mbps)	<p>The download speed is defined as the data transmission rate that is achieved for downloading a test file from a test server to a test device.</p> <p>Download Speed = Total bytes transferred during download / Total time for transfer</p> <ul style="list-style-type: none"> 80th percentile (upper range) & 20th percentile (lower range) value has been calculated for download throughput in dynamic drive and Hotspot combine data
Upload Speed (Mbps)	<p>The upload speed is the data transmission rate that is achieved for uploading a test file from a test device to a test server.</p> <p>Upload Speed = Total bytes transferred during upload / Total time for transfer.</p> <ul style="list-style-type: none"> 80th percentile (upper range) & 20th percentile (lower range) value has been calculated for upload throughput in dynamic drive and Hotspot combine data.

Download Session Setup Success Rate	(total download session established (successfully connected to server)/ total download session attempt) *100. This KPI has been calculated for Hotspot only.
Upload Session Setup Success Rate	(total upload session established (successfully connected to server)/ total upload session attempt)*100. This KPI need to report for Hotspot only.
Web Page Download Time	Web browsing test is used to measure performance in terms of opening a web/HTTP page. Time taken to open the web page successfully is considered as web browsing delay/web page download time.
Video Streaming Delay	The Video streaming delay is time taken from start of video transfer to First video frame displayed in player.
Latency	Latency is the time it takes for a small data set to be transmitted from a device to a server on the Internet and back to the same device again. The Latency is measured in milliseconds (ms). To calculate the one-way latency we just do half of the round-trip time. 50th percentile of one way latency has been reported.
Jitter	Measure of variation in time in arrival of packets from a source to destination The consideration of packet delay jitter is considered by standard deviation of Inter Packet Delay Variation. If IPDV is used. By standard deviation is meant the average of standard deviation of IPDV on DL $IPDV(i) = D(i) - D(i-1)$ then Stdvs of IPDV is considered as jitter.
Packet Loss Rate	Number of packets lost out of total packet transferred during test. Packet loss rate = (Total packet lost / Total packet sent) *100 * Packet delay (using ping) >90 ms considered as packet loss and included in packet loss rate. * Packet loss rate is calculated based on ICMP * 90th percentile for Packet loss rate has been reported in overall Hotspot performance summary.

Table-45: Network performance parameter and definition Data

Disclaimer: The observations presented above and, in the reports, represent the performance of the service providers on the area/route under test on the day/time of conducting the drive test and no inference whatsoever may be drawn regarding the quality of the telecom service by the service providers in the whole city/state/licensed service area.