



TELECOM REGULATORY AUTHORITY OF INDIA

Independent Drive Test Report

Gujarat LSA

Sep 2026

Contents

1. Introduction	3
2. Executive Summary (LSA)	3
2.1 Drive test details	3
2.2 Drive test routes	4
2.3 Summary of areas covered	4
2.4 Telecom service providers detected frequency bands	5
2.5 Key findings of Independent Drive Test.....	6
3. QoS performance analysis-LSA level.....	8
3.1 Overview.....	9
3.2 Voice performance.....	9
3.3 Data performance.....	12
4. Detailed QoS performance analysis	14
4.1 Overview.....	14
4.2 City	14
4.2.1 Drive test route.....	14
4.2.2 Areas covered	14
4.2.3 Voice performance.....	14
4.2.4 Data performance.....	27
4.3 Hotspots	35
4.3.1 Locations.....	35
4.3.2 Hotspot covered	35
4.3.3 Voice performance.....	35
4.3.4 Data performance (Auto-selection mode 5G/4G/3G/2G)	37
4.3.5 Data performance (5G Only & 4G Only Download & Upload Speed)	41
4.4 Highway	43
4.4.1 Drive test route.....	43
4.4.2 Routes Covered.....	43
4.4.3 Voice performance.....	43
4.4.4 Data performance.....	56
5. Voice & Data Key findings.....	64
5.1 Overall Voice.....	64
5.2 Overall Data	64
5.3 Operator wise Key Findings.....	65
6. Annexure	68

6.1 Route wise coverage map	68
6.1.1 City	68
6.1.2 Highway	73
7. Appendix	79
7.1 Appendix-I	79
7.1.1 Drive test setup	79
7.1.2 Drive test Methodology	81
7.2 Appendix-II	83
7.2.1 Network Performance Parameters for Voice calls	83
7.2.2 Network Performance Parameters Data tests	84

1. Introduction

TRAI Act, 1997 mandates the Authority to ensure the services delivered through various telecommunications networks meet the required quality standards prescribed, to protect the interest of the consumers of telecommunication services. TRAI is also responsible for conducting the periodical audit of such services provided by the service providers so as to protect the interests of the consumers of telecommunications services.

Accordingly, TRAI has engaged M/s RedMango Analytics Pvt. Ltd. to undertake assessment of Quality of Service of mobile service through Independent Drive Test (IDT).

In IDT, the performance of all service providers providing service in a Licensed Service Area (LSA) through various technologies (like 2G/ 3G/ 4G/ 5G) for voice and data are measured by conducting drive test. The drive test routes are finalised based on various objective criteria like reported network performance, consumer complaints etc. Methodology adopted for conducting IDT is elaborated in **APPENDIX-I**.

2. Executive Summary (LSA)

2.1 Drive test details

This report covers the findings of the IDT undertaken in Gujarat License Service Area (LSA) during the month of September-2026 under the supervision of TRAI Regional Office (RO) Jaipur. Details of route/area covered during the IDT are as given below:

S. No	Drive test route	Type of route	Distance covered (KMs)	From date	To date
1	Kachchh area including Gandhidham & Bhuj	City	245.2	08-Sep-2026	11-Sep-2026
2	Gandhidham	Inter Operator Calling	1 Location	11-Sep-2026	11-Sep-2026
3	Kachchh area including Gandhidham & Bhuj	Hotspot	9 Locations	08-Sep-2026	11-Sep-2026
4	Bhuj to Bhachau	Highway	75.7	09-Sep-2026	09-Sep-2026

Table-1: Drive test summary.

2.2 Drive test routes

The map provides overview of drive test routes indicating city drive, Inter-operator call test, hotspots and highway as per the legends shown on the map.




Figure-1: Drive test routes.

2.3 Summary of areas covered

- a) City-** Sukhpar, Uma Nagar, Airport Ring Road, Sanskar Nagar, Din Dayal Nagar, Junavas, Somiya Nagar, Anjar, Jalaram Nagar, Bharat Nagar, Gandhidham, Vinayak Society, Kandla, Mundra etc.
- b) Hotspot**
 - 1. Bhuj Bus Port
 - 2. Gandhidham Bus Stand
 - 3. Gandhidham Railway Station
 - 4. GK General Hospital Bhuj
 - 5. Government Hospital Gandhidham
 - 6. GSRTC Anjar Bus Stand
 - 7. Hamirsar Lake
 - 8. Lilashah Nagar Market
 - 9. Mundra Bus Stand
- c) Highway-** Bhuj to Bhachau via Danda Bazar, Bhuj-Bhachau Highway, Padhar, Kaniyabe, Budharmora, Amardi, Kumbhardi, Euro Colony, Madina Nagar etc.

2.4 Telecom service providers detected frequency bands

Technologies covered during the IDT and frequency bands in use are summarised in table below:

S.no.	Name of TSP	Technology	Frequency Bands (In MHz)
1	Bharti Airtel Ltd.	2G	1800
2	Bharti Airtel Ltd.	4G	900,1800,2100,2300
3	Bharti Airtel Ltd.	5G	3500
4	BSNL	2G	900
5	BSNL	4G	700,2100,2500
6	Reliance JIO Infocomm Ltd.	4G	850,1800,2300
7	Reliance JIO Infocomm Ltd.	5G	700,3500
8	Vodafone Idea Ltd.	2G	900
9	Vodafone Idea Ltd.	4G	900,1800,2100,2500
10	Vodafone Idea Ltd.	5G	3500

Table-2: Telecom service provider (TSP) covered in IDT.

2.5 Key findings of Independent Drive Test

1. Drive Test Area: The overall mobile network performance across Kachchh area including Gandhidham & Bhuj (Gujarat LSA) for the key Parameters has been summarized below:

a) Coverage Gap - The signal strength observed during voice testing on the drive test route in auto-selection mode (5G/4G/3G/2G). (refer figure- 26 to 29)

Parameter	AIRTEL	BSNL	RJIL	VIL
Total Number of Samples captured on Drive test route	56687	56051	55391	56876
Number of Samples having poor signal strength	242	575	290	245
Number of Samples having limited service (No Coverage)	0	0	0	0

b) Dropped Calls - The TSP-wise details of dropped calls in auto selection mode (5G/4G/3G/2G). (refer figure 15 to 16)

Parameter	AIRTEL	BSNL	RJIL	VIL
Number of successful Calls Established	496	496	495	499
Number of dropped Calls	0	10	3	0

c) Call Silence Instance - The TSP-wise details of Call silence instance in Auto-selection mode (5G/4G). (refer figure- 17 to 19)

Parameter	AIRTEL	BSNL	RJIL	VIL
Call Established (within service provider network)	460	459	462	476
Number of silences calls for >3 Sec	0	6	6	2
Total number of silence instances for >3 Sec	0	6	7	4

d) Packet loss rate Downlink & Uplink- The TSP-wise details of packet loss rate in downlink & uplink for Auto-selection mode (5G/4G).

Parameter	AIRTEL	BSNL	RJIL	VIL
Call Established (within service provider network)	460	459	462	476
Packet loss Rate Downlink %	0.17	1.52	0.93	0.42
Packet loss Rate Uplink %	0.22	2.40	0.79	0.39

e) Data Download and Upload Throughput-

i) Data Download Throughput: The TSP-wise details of **Average Download (DL) throughput** against declared typical DL Throughput for month, in Auto-selection mode (5G/4G/3G/2G). (refer figure- 31 to 34)

Parameter	Measured in	AIRTEL (upto 5G)	BSNL (upto 4G)	RJIL (upto 5G)	VIL (upto 5G)
Typical Download Throughput declared by TSP	(Mbits/s)	23.00	5.00	15.00	15.00
Average Download Throughput measured during IDT	(Mbits/s)	177.25	10.27	231.92	31.68

ii) Data Upload Throughput: The TSP-wise details of **Average Upload (UL) throughput** against declared typical UL Throughput for month, in Auto-selection mode (5G/4G/3G/2G). (refer figure- 35 to 38)

Parameter	Measured in	AIRTEL (upto 5G)	BSNL (upto 4G)	RJIL (upto 5G)	VIL (upto 5G)
Typical Upload Throughput declared by TSP	(Mbits/s)	10.00	3.00	7.00	8.00
Average Upload Throughput measured during IDT	(Mbits/s)	34.26	7.32	29.44	16.86

2. Drive Test Route: The overall mobile network performance on Bhuj to Bhachau Highway route (Gujarat LSA) for the key parameters has been summarised below:

a) Coverage Gap - The signal strength observed during voice testing on the drive test route in auto-selection mode (5G/4G/3G/2G). (refer figure- 64 to 67)

Parameter	AIRTEL	BSNL	RJIL	VIL
Total Number of Samples captured on Drive test route	11015	10423	10902	11198
Number of Samples having poor signal strength	202	1718	187	164
Number of Samples having limited service (No Coverage)	0	189	0	0

b) Dropped Calls - The TSP-wise details of dropped calls in auto selection mode (5G/4G/3G/2G). (refer figure-54 & 55)

Parameter	AIRTEL	BSNL	RJIL	VIL
Number of successful Calls Established	54	56	54	55
Number of dropped Calls	0	7	0	1

c) Call Silence Instance - The TSP-wise details of Call silence instance in Auto-selection mode (5G/4G). (refer figure- 56 to57)

Parameter	AIRTEL	BSNL	RJIL	VIL
Call Established (within service provider network)	53	61	52	55
Number of silences calls for >3 Sec	0	0	1	1
Total number of silence instances for >3 Sec	0	0	1	1

d) Packet loss rate Downlink & Uplink- The TSP-wise details of packet loss rate in downlink & uplink for Auto-selection mode (5G/4G).

Parameter	AIRTEL	BSNL	RJIL	VIL
Call Established (within service provider network)	53	61	52	55
Packet loss Rate Downlink %	0.50	3.88	0.98	1.11
Packet loss Rate Uplink %	0.43	4.19	0.65	1.12

e) Data Download and Upload Throughput-

i) Data Download Throughput: The TSP-wise details of **Average Download (DL) throughput** against declared typical DL Throughput for month, in Auto-selection mode (5G/4G/3G/2G). (refer figure- 69 to 72)

Parameter	Measured in	AIRTEL (upto 5G)	BSNL (upto 4G)	RJIL (upto 5G)	VIL (upto 5G)
Typical Download Throughput declared by TSP	(Mbits/s)	23.00	5.00	15.00	15.00
Average Download Throughput measured during IDT	(Mbits/s)	139.15	10.66	241.22	22.97

ii) Data Upload Throughput: The TSP-wise details of **Average Upload (UL) throughput** against declared typical UL Throughput for month, in Auto-selection mode (5G/4G/3G/2G). (refer figure- 73 to 76)

Parameter	Measured in	AIRTEL (upto 5G)	BSNL (upto 4G)	RJIL (upto 5G)	VIL (upto 5G)
Typical Upload Throughput declared by TSP	(Mbits/s)	10.00	3.00	7.00	8.00
Average Upload Throughput measured during IDT	(Mbits/s)	17.68	3.80	19.41	13.80

QoS Performance Analysis- Gujarat LSA

3. QoS performance analysis-LSA level

3.1 Overview

This section provides summary of overall QoS performance of the telecom service provider's network in the LSA by aggregating the results of drive tests conducted in the Gujarat LSA during the month of September-2026 covering city drive, hotspots and highway. (Refer Table-1)

3.2 Voice performance

(a) Voice Call Performance in 3G/2G network mode only: 3G/2G network mode testing has been done to reflect experience for respective users as they have only 3G/2G compatible handsets.

Parameters	Service Provider		
	3G/2G network mode only		
	AIRTEL	BSNL	VIL
Call Attempts	539	571	515
Call Setup Success Rate %	98.14	86.51	99.61
Drop Call Rate %	0.00	0.20	0.19
Call Setup Time-Average (Second)	4.59	4.06	4.02
Handover Success Rate %	99.50	99.78	99.46

Table-3: Summary of voice call performance in 3G/2G network mode only.




Figure-2: Call setup success rate and drop call rate performance.

Number of unique cell Id's covered in Voice test- Technology wise			
Technology	Service Provider		
	3G/2G network mode only		
	AIRTEL	BSNL	VIL
3G	NA	0	NA
2G	471	170	517

Table-4: Technology wise number of network cell Id's latched during drive test.

Note-

- RJIL does not have 3G/2G network.
- NA- Service provider doesn't provide services in respective technology.

(b) Voice Call Performance in auto network selection mode (5G/4G/3G/2G)

Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempts	640	653	639	644
Call Setup Success Rate %	100.00	98.32	100.00	100.00
Drop Call Rate %	0.00	2.80	0.47	0.16
Call Setup Time-Average (Second)	0.44	0.83	0.52	0.76
Handover Success Rate %	99.92	100.00	99.97	100.00

Table-5: Summary of voice call performance in network auto-selection mode.




Figure-3: Performance for call setup success rate and drop call rate.

Parameter	Service Provider			
	Mobile-to-Mobile (5G/4G – Open Mode)			
	AIRTEL	BSNL	RJIL	VIL
Call Established (within service provider Network)	513	520	514	531
Number of silences call for >4 Sec	0	4	3	3
Silence Call Rate %	0.00	0.77	0.58	0.56
Number of silence instances for >4 Sec	0	4	3	5
Number of silence instances for >3 Sec	0	6	8	5
Number of silence instances for >2 sec	1	8	17	7
RTP Jitter (4G & 5G) in ms	5.53	5.96	17.57	8.61
Packet loss Rate Downlink %	0.21	1.80	0.94	0.49
Packet loss Rate Uplink %	0.24	2.60	0.78	0.46

Table-6: Summary of silence instances & packet loss rate for mobile to mobile calls.

Number of unique cell Id's covered in Voice test- Technology wise				
Technology	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
5G	0	NA	698	0
4G	859	301	282	880
3G	NA	0	NA	NA
2G	0	11	NA	1

Table-7: Technology wise number of network cell Id's latched during drive test.

Note-

- NA- Service provider doesn't provide services in respective technology.
- 0- No cell Id's were found in respective technology.

(c) Mean Opinion Score (MOS) performance for speech quality:

Mean opinion score indicates quality of speech observed during the drive test across different technologies. This parameter has been calculated for mobile-to-mobile calls made within same operator network in auto mode (5G/4G/3G/2G). As per ITU-T Recommendation P.863.1, MOS values means: 5-Excellent, 4-Good, 3-Fair, 2-Poor, 1-Bad.

Speech Quality (MOS) distribution	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
Total Number of MOS Samples for calls table-6	3572	3331	3720	3860
Speech Quality (Average MOS)	4.03	3.67	4.49	4.57
Number of samples with MOS ≥ 4 to < 5 (Excellent)	3065	2174	3297	3589
Number of samples with MOS ≥ 3 to < 4 (Good)	438	536	254	205
Number of samples with MOS ≥ 2 to < 3 (Fair)	47	348	77	21
Number of samples with MOS ≥ 1 to < 2 (Poor)	22	273	92	45
%age of samples with MOS ≥ 4 to < 5 (Excellent)	85.81%	65.27%	88.63%	92.98%
%age of samples with MOS ≥ 3 to < 4 (Good)	12.26%	16.09%	6.83%	5.31%
%age of samples with MOS ≥ 2 to < 3 (Fair)	1.32%	10.45%	2.07%	0.54%
%age of samples with MOS ≥ 1 to < 2 (Poor)	0.62%	8.20%	2.47%	1.17%

Table-8: Summary of speech quality (MOS) samples.




Figure- 4: Distribution of samples in MOS range.

(d) Inter-service provider voice call performance: To check the performance of inter-service providers call setup success rate, total 15 inter operator calls were attempted at one location which is Hotel Silver Rock near Gandhidham Railway Station. The call setup success rate and call setup time observation is as below.

Call Setup Success Rate %				
From Service Provider	To Service Provider			
	AIRTEL	BSNL	RJIL	VIL
AIRTEL	NA	100.00	100.00	100.00
BSNL	93.33	NA	100.00	100.00
RJIL	100.00	100.00	NA	100.00
VIL	100.00	100.00	100.00	NA

Table-9: Call setup success rate across service providers.

Note-

- NA- Only inter-operator calls were measured during test.

Call setup time average (seconds)				
From Service Provider	To Service Provider			
	AIRTEL	BSNL	RJIL	VIL
AIRTEL	NA	3.64	1.86	0.85
BSNL	3.14	NA	1.69	1.64
RJIL	3.15	2.83	NA	1.26
VIL	1.71	1.61	0.96	NA

Table-10: Call setup time across service providers.

Note-

- NA- Only inter-operator calls were measured during test.

3.3 Data performance

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Parameters		Service Provider			
		Auto-selection mode (5G/4G/3G/2G)			
		AIRTEL	BSNL	RJIL	VIL
Download Throughput (Mbits/s)	Average	174.48	10.09	228.60	29.78
	80 th Percentile	259.45	13.96	352.44	46.11
	20 th Percentile	78.91	3.66	84.75	13.32
Upload Throughput (Mbits/s)	Average	32.54	6.89	27.43	15.99
	80 th Percentile	56.49	12.13	48.01	24.84
	20 th Percentile	8.69	1.41	7.14	6.29
Latency (ms)	50 th Percentile	28.46	43.95	30.63	24.75

Table-11: Summary of data performance in network auto-selection mode.




Figure- 5: Download and Upload throughput.

Number of unique cell Id's covered in Data test- Technology wise				
Technology	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
5G	0	NA	564	0
4G	862	381	135	919
3G	NA	0	NA	NA
2G	0	6	NA	7

Table-12: Technology wise number of network cell Id's latched during drive test.

Note-

- NA- Service provider doesn't provide services in respective technology.
- 0- No cell Id's were found in respective technology.

Detailed QoS Performance Analysis

Parameters	Service Provider		
	3G/2G network mode only		
	AIRTEL	BSNL	VIL
Call Attempts	482	467	464
Call Setup Success Rate %	97.93	99.79	99.57
Drop Call Rate %	0.00	0.00	0.22
Call Setup Time-Average (Second)	4.59	3.96	4.04
Handover Success Rate %	99.58	99.77	99.39

Table-13: Summary of voice call performance in 3G/2G network mode only.




Figure-7: Performance for call setup success rate.




Figure-8: Performance for drop call rate.

(b) Network Technology: This section represents time spent on various network technologies.

Technology	Service Provider		
	AIRTEL	BSNL	VIL
3G	NA	0.00%	NA
2G	99.97%	100.00%	100.00%
Limited Service	0.03%	0.00%	0.00%

Table-14: Time spent on technology during drive test 3G/2G network mode.

Note-

- NA- Service provider doesn't provide services in respective technology.




Figure-9: Serving technology plots 3G/2G network mode - AIRTEL.




Figure- 10: Serving technology plots 3G/2G network mode - BSNL.




Figure-11: Serving technology plots 3G/2G network mode - VIL.

(c) Network Signal Strength Distribution: The following chart represents signal strength distribution for 3G/2G network mode only. (Refer figure- 82, 83 & 84 for map view)




Figure-12: Signal strength distribution 3G/2G network mode only.

Observations:

- Airtel has 56% of samples falling in the excellent signal strength category.
- BSNL has 27% of samples falling in the excellent signal strength category.
- VIL has 40% of samples falling in the excellent signal strength category.

(d) Voice Call Performance in auto network selection mode (5G/4G/3G/2G)

Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempts	496	500	495	499
Call Setup Success Rate %	100.00	99.20	100.00	100.00
Drop Call Rate %	0.00	2.02	0.61	0.00
Call Setup Time Average (Second)	0.44	0.82	0.51	0.75
Handover Success Rate %	99.90	100.00	99.97	100.00

Table-15: Summary of voice call performance in network auto-selection mode.




Figure-13: Performance for call setup success rate.




Figure-14: Performance for drop call rate.



Figure-15: Drop call locations in auto-selection mode (5G/4G/3G/2G) voice - BSNL.




Figure-16: Drop call locations in auto-selection mode (5G/4G/3G/2G) voice - RJIL.

Parameter	Service Provider			
	Mobile-to-Mobile (5G/4G – Open Mode)			
	AIRTEL	BSNL	RJIL	VIL
Call Established (within service provider Network)	460	459	462	476
Number of silences call for >4 Sec	0	4	3	2
Silence Call Rate %	0.00	0.87	0.65	0.42
Number of silence instances for >4 Sec	0	4	3	4
Number of silence instances for >3 Sec	0	6	7	4
Number of silence instances for >2 sec	0	7	15	4
RTP Jitter (4G & 5G) in ms	5.29	5.88	17.98	8.21
Packet loss Rate Downlink %	0.17	1.52	0.93	0.42
Packet loss Rate Uplink %	0.22	2.40	0.79	0.39

Table-16: Summary of silence instances & packet loss rate for mobile to mobile call.




Figure-17: Number of silence instances for >3 Sec Mobile-to-Mobile (5G/4G-Open Mode) - BSNL.




Figure-18: Number of silence instances for >3 Sec Mobile-to-Mobile (5G/4G-Open Mode) - RJIL.




Figure-19: Number of silence instances for >3 Sec Mobile-to-Mobile (5G/4G-Open Mode) - VIL.

(e) Mean Opinion Score (MOS) performance for speech quality:

Mean opinion score indicate quality of speech observed during the drive test across different technologies. This parameter has been calculated for mobile to mobile calls made within same operator network in auto mode (5G/4G/3G/2G). As per ITU-T Recommendation P.863.1, MOS value means: 5-Excellent, 4-Good, 3-Fair, 2-Poor, 1-Bad.

Speech Quality (MOS) distribution	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
Total Number of MOS Samples for calls in table-16	2888	2756	3058	3146
Speech Quality (Average MOS)	4.05	3.69	4.48	4.58
Number of samples with MOS ≥ 4 to < 5 (Excellent)	2527	1824	2693	2934
Number of samples with MOS ≥ 3 to < 4 (Good)	316	428	216	167
Number of samples with MOS ≥ 2 to < 3 (Fair)	31	283	70	16
Number of samples with MOS ≥ 1 to < 2 (Poor)	14	221	79	29
%age of samples with MOS ≥ 4 to < 5 (Excellent)	87.50%	66.18%	88.06%	93.26%
%age of samples with MOS ≥ 3 to < 4 (Good)	10.94%	15.53%	7.06%	5.31%
%age of samples with MOS ≥ 2 to < 3 (Fair)	1.07%	10.27%	2.29%	0.51%
%age of samples with MOS ≥ 1 to < 2 (Poor)	0.48%	8.02%	2.58%	0.92%

Table-17: Summary of speech quality (MOS) samples.




Figure-20: Distribution of samples in MOS range.

(f) Network Technology: This section represents time spent on various network technologies.

Technology	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
5G	10.42%	NA	93.97%	1.97%
4G	89.58%	99.26%	6.03%	98.03%
3G	NA	0.00%	NA	NA
2G	0.00%	0.74%	NA	0.00%
Limited Service	0.00%	0.00%	0.00%	0.00%

Table-18: Time spent on technology during drive test in auto-selection mode (5G/4G/3G/2G) voice.

Note-

- NA- Service provider doesn't provide services in respective technology.




Figure-21: Serving technology plots in auto-selection mode (5G/4G/3G/2G) voice - AIRTEL.




Figure-22: Serving technology plots in auto-selection mode (5G/4G/3G/2G) voice - BSNL.




Figure-23: Serving technology plots in auto-selection mode (5G/4G/3G/2G) voice - RJIL.




Figure-24: Serving technology plots in auto-selection mode (5G/4G/3G/2G) voice - VIL.

(g) Network Signal Strength Distribution: The following chart provides signal strength distribution for auto-selection mode (5G/4G/3G/2G) voice. (Refer figure-85, 86, 87 & 88 for map view)




Figure-25: Signal strength distribution auto-selection mode (5G/4G/3G/2G) voice.

Observations:

- Airtel has 35% of samples falling in the excellent signal strength category.
- BSNL has 28% of samples falling in the excellent signal strength category.
- RJIL has 54% of samples falling in the excellent signal strength category.
- VIL has 44% of samples falling in the excellent signal strength category.

(h) Coverage Gap observed




Figure-26: Poor coverage & no coverage locations in auto-selection mode (5G/4G/3G/2G) voice-AIRTEL.



Figure-27: Poor coverage & no coverage locations in auto-selection mode (5G/4G/3G/2G) voice-BSNL.




Figure-28: Poor coverage & no coverage locations in auto-selection mode (5G/4G/3G/2G) voice-RJIL.




Figure-29: Poor coverage & no coverage locations in auto-selection mode (5G/4G/3G/2G) voice-VIL.

4.2.4 Data performance

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Parameters		Service Provider			
		Auto-selection mode (5G/4G/3G/2G)			
		AIRTEL	BSNL	RJIL	VIL
Download Throughput (Mbits/s)	Average	177.25	10.27	231.92	31.68
	80 th Percentile	259.90	13.94	351.30	47.67
	20 th Percentile	90.72	4.03	95.80	14.71
Upload Throughput (Mbits/s)	Average	34.26	7.32	29.44	16.86
	80 th Percentile	57.33	13.09	52.49	26.76
	20 th Percentile	10.68	1.68	8.14	6.71
Latency (ms)	50 th Percentile	28.93	40.88	29.87	23.73

Table-19: Summary of Data performance in network auto-selection mode.




Figure- 30: Download & Upload throughput.




Figure-31: Download throughput distribution auto-selection mode (5G/4G/3G/2G) - AIRTEL.




Figure-32: Download throughput distribution auto-selection mode (5G/4G/3G/2G) - BSNL.




Figure-33: Download throughput distribution auto-selection mode (5G/4G/3G/2G) - RJIL.




Figure-34: Download throughput distribution auto-selection mode (5G/4G/3G/2G) - VIL.




Figure-35: Upload throughput distribution auto-selection mode (5G/4G/3G/2G) - AIRTEL.




Figure-36: Upload throughput distribution auto-selection mode (5G/4G/3G/2G) - BSNL.




Figure-37: Upload throughput distribution auto-selection mode (5G/4G/3G/2G) - RJIL.




Figure-38: Upload throughput distribution auto-selection mode (5G/4G/3G/2G) - VIL.

(b) Network Technology: This section represents time spent on various network technologies.

Technology	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
5G	90.51%	NA	97.45%	45.87%
4G	9.49%	99.72%	2.55%	54.08%
3G	NA	0.00%	NA	NA
2G	0.00%	0.09%	NA	0.05%
Limited Service	0.00%	0.19%	0.00%	0.00%

Table-20: Time spent on technology during drive test in auto-selection mode (5G/4G/3G/2G) data.

Note-

- NA- Service provider doesn't provide services in respective technology.




Figure-39: Serving technology plots in auto-selection mode (5G/4G/3G/2G) data - AIRTEL.




Figure-40: Serving technology plots in auto-selection mode (5G/4G/3G/2G) data - BSNL.




Figure-41: Serving technology plots in auto-selection mode (5G/4G/3G/2G) data - RJIL.




Figure-42: Serving technology plots in auto-selection mode (5G/4G/3G/2G) data - VIL.

(c) Network Signal Strength Distribution: The following chart provides signal strength distribution for auto-selection mode (5G/4G/3G/2G) data. (Refer figure-89, 90, 91 & 92 for map view)




Figure-43: Signal strength distribution auto-selection mode (5G/4G/3G/2G) data.

Observations:

- Airtel has 32% of samples falling in the excellent signal strength category.
- BSNL has 5% of samples falling in the excellent signal strength category.
- RJIL has 20% of samples falling in the excellent signal strength category.
- VIL has 24% of samples falling in the excellent signal strength category.

4.3 Hotspots

Hotspot testing has been done from 8th September 2026 to 11th September 2026. Nine locations have been tested in Kachchh area including Gandhidham & Bhuj. (Refer Table-1)

4.3.1 Locations




Figure- 44: Hotspot locations.

4.3.2 Hotspot covered

1. Bhuj Bus Port
2. Gandhidham Bus Stand
3. Gandhidham Railway Station
4. GK General Hospital Bhuj
5. Government Hospital Gandhidham
6. GSRTC Anjar Bus Stand
7. Hamirsar Lake
8. Lilashah Nagar Market
9. Mundra Bus Stand

4.3.3 Voice performance

Overall Voice Performance				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	90	90	90	90
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	1.11	0.00	0.00
Call Setup Time-Average (Second)	0.46	0.72	0.48	0.71

Table-21: Overall summary of voice call performance in network auto-selection mode (5G/4G/3G/2G).

Bhuj Bus Port				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	0.44	0.60	0.55	0.79

Table-22: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G)

Gandhidham Bus Stand				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	0.72	0.78	0.47	0.79

Table-23: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G)

Gandhidham Railway Station				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	0.58	0.77	0.39	0.74

Table-24: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G)

GK General Hospital Bhuj				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	0.33	0.55	0.56	0.74

Table-25: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G)

Government Hospital Gandhidham				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	0.42	0.77	0.58	0.61

Table-26: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G)

GSRTC Anjar Bus Stand				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	10.00	0.00	0.00
Call Setup Time-Average (Second)	0.47	0.94	0.40	0.68

Table-27: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G)

Hamirsar Lake				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	0.42	0.57	0.43	0.76

Table-28: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G)

Lilashah Nagar Market				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	0.38	0.80	0.45	0.66

Table-29: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G)

Mundra Bus Stand				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempt	10	10	10	10
Call Setup Success Rate %	100.00	100.00	100.00	100.00
Drop Call Rate %	0.00	0.00	0.00	0.00
Call Setup Time-Average (Second)	0.37	0.70	0.46	0.64

Table-30: Summary of voice call performance in network auto-selection mode(5G/4G/3G/2G)

4.3.4 Data performance (Auto-selection mode 5G/4G/3G/2G)

Overall Data Performance				
Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	217.13	7.61	172.65	24.22
Download Throughput 80 th Percentile (Mbit/s)	301.81	11.59	286.85	42.79
Download Throughput 20 th Percentile (Mbit/s)	121.30	2.06	49.60	7.15
Download Session Setup Success Rate %	100.00	100.00	95.56	100.00
Upload Throughput Average (Mbits/s)	44.18	7.94	22.01	11.46
Upload Throughput 80 th Percentile (Mbit/s)	63.62	11.74	37.23	17.81
Upload Throughput 20 th Percentile (Mbit/s)	8.35	2.15	9.80	6.32
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	5.69	5.17	4.28	4.33
Youtube Initial Buffer Delay (Second)	1.41	2.05	1.27	1.48
Latency (ms) – 50 th Percentile	26.46	60.31	32.17	25.06
Jitter (ms)	6.22	28.21	5.52	6.88
Packet Loss Rate%	6.57	8.61	0.33	0.27
Packet Loss Rate- 90 th percentile	32.12	18.00	1.04	0.52

Table-31: Overall Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Bhuj Bus Port				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	238.85	4.50	315.91	20.70
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	62.10	9.77	55.96	15.94
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	5.99	4.02	3.70	6.15
Youtube Initial Buffer Delay (Second)	0.73	2.31	1.20	0.84
Latency (ms) – 50th Percentile	26.76	47.15	32.47	24.42
Jitter (ms)	1.76	32.68	3.39	1.32
Packet Loss Rate%	0.10	4.00	0.00	0.00

Table-32: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Gandhidham Bus Stand				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	102.03	4.05	126.71	6.81
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	55.71	14.90	17.51	9.50
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	4.08	3.23	5.14	3.45
Youtube Initial Buffer Delay (Second)	0.66	2.12	1.46	2.28
Latency (ms) – 50th Percentile	23.26	79.78	30.25	28.52
Jitter (ms)	2.61	31.62	4.84	3.51
Packet Loss Rate%	0.40	13.80	0.00	0.10

Table-33: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Gandhidham Railway Station				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	17.62	28.91	42.46	13.83
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	6.55	12.46	12.53	7.84
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	7.86	6.88	5.69	2.72
Youtube Initial Buffer Delay (Second)	1.49	1.37	1.49	1.02
Latency (ms) – 50th Percentile	65.70	60.34	44.29	28.65
Jitter (ms)	23.80	26.19	10.69	12.70
Packet Loss Rate%	34.80	9.60	0.90	0.30

Table-34: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

GK General Hospital Bhuj				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	503.47	4.18	211.46	37.10
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	58.67	4.21	37.76	17.81
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	6.94	3.71	4.44	3.81
Youtube Initial Buffer Delay (Second)	1.93	1.41	0.88	0.91
Latency (ms) – 50 th Percentile	24.76	63.41	33.28	22.65
Jitter (ms)	2.03	37.49	3.11	4.05
Packet Loss Rate%	0.10	2.30	0.00	0.10

Table-35: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Government Hospital Gandhidham				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	156.84	2.99	403.48	31.27
Download Session Setup Success Rate%	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	2.73	9.16	35.82	8.47
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	9.06	5.39	3.83	4.94
Youtube Initial Buffer Delay (Second)	4.53	1.29	1.08	1.12
Latency (ms)- 50 th Percentile	25.38	78.33	26.65	19.75
Jitter (ms)	10.09	26.89	3.72	3.61
Packet Loss Rate%	23.60	11.80	0.00	0.10

Table-36: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

GSRTC Anjar Bus Stand				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	211.90	1.97	179.72	42.59
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	56.64	1.72	9.65	21.52
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	3.79	3.75	4.41	3.06
Youtube Initial Buffer Delay (Second)	0.64	1.86	1.38	0.66
Latency (ms) – 50 th Percentile	28.49	79.80	31.84	25.43
Jitter (ms)	2.19	27.12	2.83	6.17
Packet Loss Rate%	0.00	19.50	0.10	0.10

Table-37: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Hamirsar Lake				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	194.52	5.87	67.66	36.92
Download Session Setup Success Rate%	100.00	100.00	80.00	100.00
Upload Throughput Average (Mbits/s)	53.17	13.51	10.94	15.82
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	3.97	5.73	4.22	3.90
Youtube Initial Buffer Delay (Second)	0.69	1.34	1.02	0.89
Latency (ms)- 50 th Percentile	26.05	43.18	31.44	26.93
Jitter (ms)	6.46	2.44	3.41	2.50
Packet Loss Rate%	0.00	0.10	0.20	0.00

Table-38: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Lilashah Nagar Market				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	153.32	4.54	4.18	5.73
Download Session Setup Success Rate %	100.00	100.00	80.00	100.00
Upload Throughput Average (Mbits/s)	47.77	0.92	5.04	5.34
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	6.60	7.89	2.98	4.39
Youtube Initial Buffer Delay (Second)	2.56	4.56	1.83	1.03
Latency (ms) – 50 th Percentile	27.47	48.53	54.86	20.45
Jitter (ms)	3.17	39.07	10.62	19.16
Packet Loss Rate%	0.00	9.00	1.70	1.30

Table-39: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

Mundra Bus Stand				
Parameters	Service Provider			
	Auto-Selection Mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Download Throughput Average (Mbits/s)	375.65	11.52	147.54	23.06
Download Session Setup Success Rate %	100.00	100.00	100.00	100.00
Upload Throughput Average (Mbits/s)	54.22	4.77	12.88	0.92
Upload Session Setup Success Rate %	100.00	100.00	100.00	100.00
Web Browsing Delay (Second)	3.35	5.32	3.74	7.09
Youtube Initial Buffer Delay (Second)	0.71	2.36	1.11	8.99
Latency (ms) – 50 th Percentile	25.63	77.86	27.59	33.57
Jitter (ms)	3.82	30.68	7.06	8.87
Packet Loss Rate%	0.10	7.40	0.10	0.40

Table-40: Summary of Data performance in network auto-selection mode (5G/4G/3G/2G).

4.3.5 Data performance (5G Only & 4G Only Download & Upload Speed)

Overall Data Performance					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	189.74	-	184.33	31.17
	Upload Throughput Average (Mbits/s)	44.96	-	25.05	14.29
4G	Download Throughput Average (Mbits/s)	58.64	10.41	49.37	27.34
	Upload Throughput Average (Mbits/s)	8.87	11.52	10.67	18.44

Table-41: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

Bhuj Bus Port					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	197.90	-	292.35	22.03
	Upload Throughput Average (Mbits/s)	60.45	-	61.36	14.94
4G	Download Throughput Average (Mbits/s)	46.04	8.37	57.94	24.51
	Upload Throughput Average (Mbits/s)	16.31	14.65	8.85	35.95

Table-42: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

Gandhidham Bus Stand					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	115.08	-	277.78	6.75
	Upload Throughput Average (Mbits/s)	56.80	-	69.17	5.02
4G	Download Throughput Average (Mbits/s)	18.39	19.99	40.28	23.33
	Upload Throughput Average (Mbits/s)	6.37	24.38	25.23	30.12

Table-43: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

Gandhidham Railway Station					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	10.05	-	52.77	-
	Upload Throughput Average (Mbits/s)	4.62	-	13.77	-
4G	Download Throughput Average (Mbits/s)	7.67	21.41	78.39	12.72
	Upload Throughput Average (Mbits/s)	1.43	13.41	3.23	8.21

Table-44: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

GK General Hospital Bhuj					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	492.08	-	204.99	29.16
	Upload Throughput Average (Mbits/s)	59.08	-	4.38	14.14
4G	Download Throughput Average (Mbits/s)	128.41	13.38	67.84	44.81
	Upload Throughput Average (Mbits/s)	16.32	19.53	13.68	21.64

Table-45: Overall Summary of 5G only & 4G only data download & upload speed.

Note- “-”Respective technology was not observed during the test.

Government Hospital Gandhidham					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	43.35	-	461.74	48.52
	Upload Throughput Average (Mbits/s)	2.54	-	33.51	8.26
4G	Download Throughput Average (Mbits/s)	26.52	3.69	85.77	27.58
	Upload Throughput Average (Mbits/s)	1.01	8.59	5.48	6.93

Table-46: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "-"Respective technology was not observed during the test.					
GSRTC Anjar Bus Stand					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	204.97	-	151.16	57.49
	Upload Throughput Average (Mbits/s)	53.66	-	11.18	38.23
4G	Download Throughput Average (Mbits/s)	159.74	4.75	39.08	37.92
	Upload Throughput Average (Mbits/s)	16.90	1.41	8.55	17.89

Table-47: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "-"Respective technology was not observed during the test.					
Hamirsar Lake					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	176.12	-	62.40	35.67
	Upload Throughput Average (Mbits/s)	52.14	-	11.38	17.11
4G	Download Throughput Average (Mbits/s)	23.96	6.86	26.20	27.50
	Upload Throughput Average (Mbits/s)	7.88	7.65	7.49	20.55

Table-48: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "-"Respective technology was not observed during the test.					
Lilashah Nagar Market					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	81.84	-	4.06	6.38
	Upload Throughput Average (Mbits/s)	38.27	-	3.76	6.27
4G	Download Throughput Average (Mbits/s)	89.08	5.61	47.40	17.39
	Upload Throughput Average (Mbits/s)	11.24	9.69	7.96	8.93

Table-49: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "-"Respective technology was not observed during the test.					
Mundra Bus Stand					
Parameters		Service Provider			
		AIRTEL	BSNL	RJIL	VIL
5G	Download Throughput Average (Mbits/s)	355.89	-	151.73	-
	Upload Throughput Average (Mbits/s)	29.11	-	16.98	-
4G	Download Throughput Average (Mbits/s)	27.95	11.51	1.40	30.29
	Upload Throughput Average (Mbits/s)	2.34	6.98	15.62	15.70

Table-50: Overall Summary of 5G only & 4G only data download & upload speed.

Note- "-"Respective technology was not observed during the test.					
---	--	--	--	--	--

4.4 Highway

Drive test has been conducted on 9th September 2026 covering one highway route. (Refer Table-1)

4.4.1 Drive test route




Figure-45: Drive test route Highway.

4.4.2 Routes Covered

Bhuj to Bhachau via Danda Bazar, Bhuj-Bhachau Highway, Padhar, Kaniyabe, Budharmora, Amardi, Kumbhardi, Euro Colony, Madina Nagar etc.

4.4.3 Voice performance

(a) Voice Call Performance in 3G/2G network mode only: 3G/2G network mode testing has been done to reflect the experience for respective users as they have only 3G/2G compatible handsets.

Parameters	Service Provider		
	3G/2G network mode only		
	AIRTEL	BSNL	VIL
Call Attempts	57	104	51
Call Setup Success Rate %	100.00	26.92	100.00
Drop Call Rate %	0.00	3.57	0.00
Call Setup Time-Average (Second)	4.63	5.74	3.90
Handover Success Rate %	98.97	100.00	100.00

Table-51: Summary of voice call performance in 3G/2G network mode only.




Figure-46: Performance for call setup success rate.




Figure-47: Performance for drop call rate.

Network Technology: This section represents time spent on various network technologies.

Technology	Service Provider		
	AIRTEL	BSNL	VIL
3G	NA	0.00%	NA
2G	100.00%	83.58%	100.00%
Limited Service	0.00%	16.42%	0.00%

Table-52: Time spent on technology during drive test 3G/2G network mode only.




Figure-48: Serving technology plots 3G/2G network mode - AIRTEL.




Figure-49: Serving technology plots 3G/2G network mode - BSNL.




Figure-50: Serving technology plots 3G/2G network mode - VIL.

(c) Network Signal Strength Distribution: The following chart represents signal strength distribution for 3G/2G network mode only. (Refer figure-93, 94 & 95 for map view)




Figure-51: Signal strength distribution 3G/2G network mode only.

Observations:

- Airtel has 35% of samples falling in the excellent signal strength category.
- BSNL has 12% of samples falling in the excellent signal strength category.
- VIL has 20% of samples falling in the excellent signal strength category.

(d) Voice Call Performance in auto network selection mode (5G/4G/3G/2G)

Parameters	Service Provider			
	Auto-selection mode (5G/4G/3G/2G)			
	AIRTEL	BSNL	RJIL	VIL
Call Attempts	54	63	54	55
Call Setup Success Rate %	100.00	88.89	100.00	100.00
Drop Call Rate %	0.00	12.50	0.00	1.82
Call Setup Time Average (Second)	0.43	1.08	0.66	0.99
Handover Success Rate %	100.00	100.00	100.00	100.00

Table-53: Summary of voice call performance in network auto-selection mode.




Figure-52: Performance for call setup success rate.




Figure-53: Performance for drop call rate.



Figure-54: Drop call locations in auto-selection mode (5G/4G/3G/2G) voice - BSNL




Figure-55: Drop call locations in auto-selection mode (5G/4G/3G/2G) voice – VIL.

Parameter	Service Provider			
	Mobile-to-Mobile (5G/4G - Open Mode)			
	AIRTEL	BSNL	RJIL	VIL
Call Established (within service provider Network)	53	61	52	55
Number of silence call for >4 Sec	0	0	0	1
Silence Call Rate %	0.00	0.00	0.00	1.82
Number of silence instances for >4 Sec	0	0	0	1
Number of silence instances for >3 Sec	0	0	1	1
Number of silence instances for >2 sec	1	1	2	3
RTP Jitter (4G & 5G) in ms	6.60	6.34	15.72	10.38
Packet loss Rate Downlink %	0.50	3.88	0.98	1.11
Packet loss Rate Uplink %	0.43	4.19	0.65	1.12

Table-54: Summary of silence instances & packet loss rate for mobile to mobile call.




Figure-56: Number of silence instances for >3 Sec Mobile-to-Mobile (5G/4G-Open Mode)- RJIL.




Figure-57: Number of silence instances for >3 Sec Mobile-to-Mobile (5G/4G-Open Mode) - VIL.

(e) Mean Opinion Score (MOS) performance for speech quality:

Mean opinion score indicate quality of speech observed during the drive test across different technologies. This parameter has been calculated for mobile to mobile calls made within same operator network in auto mode (5G/4G/3G/2G). As per ITU-T Recommendation P.863.1, MOS values means: 5-Excellent, 4-Good, 3-Fair, 2-Poor, 1-Bad.

Speech Quality (MOS) distribution	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
Total Number of MOS Samples for calls in table-54	684	575	662	714
Speech Quality (Average MOS)	3.97	3.59	4.54	4.53
Number of samples with MOS ≥ 4 to < 5 (Excellent)	538	350	604	655
Number of samples with MOS ≥ 3 to < 4 (Good)	122	108	38	38
Number of samples with MOS ≥ 2 to < 3 (Fair)	16	65	7	5
Number of samples with MOS ≥ 1 to < 2 (Poor)	8	52	13	16
%age of samples with MOS ≥ 4 to < 5 (Excellent)	78.65%	60.87%	91.24%	91.74%
%age of samples with MOS ≥ 3 to < 4 (Good)	17.84%	18.78%	5.74%	5.32%
%age of samples with MOS ≥ 2 to < 3 (Fair)	2.34%	11.30%	1.06%	0.70%
%age of samples with MOS ≥ 1 to < 2 (Poor)	1.17%	9.04%	1.96%	2.24%

Table-55: Summary of speech quality (MOS) samples.




Figure-58: Distribution of samples in MOS range.

(f) Network Technology: This section represents time spent on various network technologies.

Technology	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
5G	6.10%	NA	67.25%	0.70%
4G	93.90%	95.73%	32.75%	99.10%
3G	NA	0.00%	NA	NA
2G	0.00%	2.50%	NA	0.21%
Limited Service	0.00%	1.77%	0.00%	0.00%

Table-56: Time spent on technology during drive test in auto-selection mode (5G/4G/3G/2G) voice.

Note-

- NA- Service provider doesn't provide services in respective technology.




Figure-59: Serving technology plots in auto-selection mode (5G/4G/3G/2G) voice - AIRTEL.




Figure-60: Serving technology plots in auto-selection mode (5G/4G/3G/2G) voice - BSNL.




Figure-61: Serving technology plots in auto-selection mode (5G/4G/3G/2G) voice - RJIL.




Figure-62: Serving technology plots in auto-selection mode (5G/4G/3G/2G) voice - VIL.

(g) Network Signal Strength Distribution: The following chart provides signal strength distribution for auto-selection mode (5G/4G/3G/2G) voice. (Refer figure-96, 97, 98 & 99 for map view)




Figure-63: Signal strength distribution auto-selection mode 5G/4G/3G/2G voice.

Observations:

- Airtel has 23% of samples falling in the excellent signal strength category.
- BSNL has 8% of samples falling in the excellent signal strength category.
- RJIL has 34% of samples falling in the excellent signal strength category.
- VIL has 26% of samples falling in the excellent signal strength category.

(h) Coverage Gap observed




Figure-64: Poor coverage & no coverage locations in auto-selection mode (5G/4G/3G/2G) voice-AIRTEL.




Figure-65: Poor coverage & no coverage locations in auto-selection mode (5G/4G/3G/2G) voice-BSNL.




Figure-66: Poor coverage & no coverage locations in auto-selection mode (5G/4G/3G/2G) voice-RJIL.




Figure-67: Poor coverage & no coverage locations in auto-selection mode (5G/4G/3G/2G) voice-VIL.

4.4.4 Data performance

(a) Data Parameters (Auto-selection mode- 5G/4G/3G/2G)

Parameters		Service Provider			
		Auto-selection mode (5G/4G/3G/2G)			
		AIRTEL	BSNL	RJIL	VIL
Download Throughput (Mbps/s)	Average	139.15	10.66	241.22	22.97
	80th Percentile	237.27	17.15	368.08	34.49
	20th Percentile	24.85	3.09	83.01	8.95
Upload Throughput (Mbps/s)	Average	17.68	3.80	19.41	13.80
	80th Percentile	29.36	6.91	33.65	22.77
	20th Percentile	3.00	0.84	2.69	5.13
Latency (ms)	50th Percentile	36.40	40.73	29.86	26.87

Table-57: Summary of Data performance in network auto-selection mode.




Figure-68: Download & Upload throughput.




Figure-69: Download throughput distribution auto-selection mode (5G/4G/3G/2G) - AIRTEL.




Figure-70: Download throughput distribution auto-selection mode (5G/4G/3G/2G) - BSNL.




Figure-71: Download throughput distribution auto-selection mode (5G/4G/3G/2G) - RJIL.




Figure-72: Download throughput distribution auto-selection mode (5G/4G/3G/2G) - VIL.




Figure-73: Upload throughput distribution auto-selection mode (5G/4G/3G/2G) - AIRTEL.




Figure-74: Upload throughput distribution auto-selection mode (5G/4G/3G/2G) - BSNL.




Figure-75: Upload throughput distribution auto-selection mode (5G/4G/3G/2G) - RJIL.




Figure-76: Upload throughput distribution auto-selection mode (5G/4G/3G/2G) - VIL.

(b) Network Technology: This section represents time spent on various network technologies.

Technology	Service Provider			
	AIRTEL	BSNL	RJIL	VIL
5G	63.57%	NA	80.88%	12.10%
4G	36.43%	93.42%	19.12%	87.03%
3G	NA	0.00%	NA	NA
2G	0.00%	0.70%	NA	0.87%
Limited Service	0.00%	5.88%	0.00%	0.00%

Table-58: Time spent on technology during drive test in auto-selection mode (5G/4G/3G/2G) data.

Note-

- NA- Service provider doesn't provide services in respective technology.




Figure-77: Serving technology plot in auto-selection mode (5G/4G/3G/2G) data - AIRTEL.






Figure-78: Serving technology plot in auto-selection mode (5G/4G/3G/2G) data - BSNL.



(c) Network Signal Strength Distribution: The following chart provides signal strength distribution for auto-selection mode (5G/4G/3G/2G) data. (Refer figure-100, 101, 102 & 103 for map view)




Figure-81: Signal strength distribution auto-selection mode (5G/4G/3G/2G) data.

Observations:

- Airtel has 8% of samples falling in the excellent signal strength category.
- BSNL has 1% of samples falling in the excellent signal strength category.
- RJIL has 8% of samples falling in the excellent signal strength category.
- VIL has 14% of samples falling in the excellent signal strength category.

5. Voice & Data Key findings

5.1 Overall Voice

1. Call Setup Success Rate:

- a) Airtel, BSNL and VIL have 98.14%, 86.51% and 99.61% call setup success rate respectively in 3G/2G network mode. (refer table-3)
- b) Airtel, BSNL, RJIL and VIL have 100.00%, 98.32%, 100.00% and 100.00% call setup success rate respectively in auto-selection mode (5G/4G/3G/2G). (refer table-5)
- c) Airtel, RJIL & VIL have 100.00% call setup success rate while calling on peer service provider's network for inter-operator calls. (refer table-9)
- d) BSNL had a 100.00% call setup success when calling RJIL and VIL whereas call blocking was observed when calling Airtel. (refer table-9)

2. Call Setup Time:

- a) Airtel, BSNL and VIL call setup time is 4.59, 4.06 and 4.02 seconds respectively in 3G/2G network mode. (refer table-3)
- b) Airtel, BSNL, RJIL & VIL call setup time is 0.44, 0.83, 0.52 & 0.76 seconds respectively in auto-selection mode (5G/4G/3G/2G). (refer table-5)

3. Call Silence/Mute Rate:

In packet switched network (4G/5G) BSNL, RJIL, VIL and Airtel have 0.77%, 0.58%, 0.56% and 0.00% silence call rate respectively. Further BSNL has higher RTP packet loss rate in downlink (1.80%) compared to RJIL (0.94%), VIL (0.49%) and Airtel (0.21%). In uplink the RTP packet loss rate is higher for BSNL (2.60%) compared to RJIL (0.78%), VIL (0.46%) and Airtel (0.24%). (refer table-6)

4. Drop Call Rate:

- a) Airtel, BSNL and VIL drop call rate 0.00%, 0.20% and 0.19% respectively in 3G/2G network mode. (refer table-3)
- b) Airtel, BSNL, RJIL and VIL drop call rate 0.00%, 2.80%, 0.47% and 0.16% respectively in auto-selection mode (5G/4G/3G/2G). (refer table-5)

5.2 Overall Data

1. Data download and upload performance (Overall i.e. LSA):

- a) Airtel, BSNL, RJIL and VIL average download speeds are 174.48 Mbps, 10.09 Mbps, 228.60 Mbps and 29.78 Mbps respectively. (refer table-11)
- b) Airtel, BSNL, RJIL and VIL average upload speeds are 32.54 Mbps, 6.89 Mbps, 27.43 Mbps and 15.99 Mbps respectively. (refer table-11)

2. Data download and upload performance (static i.e. while stationary):

- a) Airtel, BSNL, RJIL and VIL average download speeds are 217.13 Mbps, 7.61 Mbps, 172.65 Mbps and 24.22 Mbps respectively. (refer table-31)
- b) Airtel, BSNL, RJIL and VIL average upload speeds are 44.18 Mbps, 7.94 Mbps, 22.01 Mbps and 11.46 Mbps respectively. (refer table-31)

3. Data session setup success rate (static i.e. while stationary):

- a) Airtel, BSNL, RJIL and VIL have 100.00%, 100.00%, 95.56% and 100.00% download session setup success rate respectively. (refer table-31)
- b) All Operators have 100.00% upload session setup success rate. (refer table-31)

5.3 Operator wise Key Findings

1. Airtel:

Voice

- 98.14% call setup success rate and 0.00% drop call rate have been observed in 3G/2G network mode for LSA. (refer table-3)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for LSA. (refer table-5)
- 97.93% call setup success rate and 0.00% drop call rate have been observed in 3G/2G network mode for city drive. (refer table-13)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. (refer table-15)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all hotspot locations. (refer table-21)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in 3G/2G network mode for highway drive. (refer table-51)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for highway drive. (refer table-53)

Data

- Airtel has 174.48 Mbps average download speed & 32.54 Mbps average upload speed for LSA. (refer table-11)
- Airtel has 177.25 Mbps average download speed & 34.26 Mbps average upload speed across measured routes for city drive. (refer table-19)
- Gandhidham Railway Station has less download speed (less than 100 Mbps) out of total 9 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-34)
- Gandhidham Railway Station & Government Hospital Gandhidham have less upload speed (less than 20 Mbps) out of total 9 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-34 & 36)
- Airtel has 139.15 Mbps average download speed & 17.68 Mbps average upload speed across measured routes for highway drive. (refer table-57)

2. BSNL:

Voice

- 86.51% call setup success rate and 0.20% drop call rate have been observed in 3G/2G network mode for LSA. (refer table-3)
- 98.32% call setup success rate and 2.80% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for LSA. (refer table-5)
- 99.79% call setup success rate and 0.00% drop call rate have been observed in 3G/2G network mode for city drive. (refer table-13)
- 99.20% call setup success rate and 2.02% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. (refer table-15)
- 100.00% call setup success rate and 1.11% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all hotspot locations. (refer table-21)

- 26.92% call setup success rate and 3.57% drop call rate have been observed in 3G/2G network mode for highway drive. (refer table-51)
- 88.89% call setup success rate and 12.50% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for highway drive. (refer table-53)

Data

- BSNL has 10.09 Mbps average download speed & 6.89 Mbps average upload speed for LSA. (refer table-11)
- BSNL has 10.27 Mbps average download speed & 7.32 Mbps average upload speed across measured routes for city drive. (refer table-19)
- Bhuj Bus Port, Gandhidham Bus Stand, GK General Hospital Bhuj, Government Hospital Gandhidham, GSRTC Anjar Bus Stand, Hamirsar Lake & Lilashah Nagar Market have less download speed (less than 10 Mbps) out of total 9 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-32, 33, 35, 36, 37, 38 & 39)
- GSRTC Anjar Bus Stand & Lilashah Nagar Market have less upload speed (less than 2 Mbps) out of total 9 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-37 & 39)
- BSNL has 10.66 Mbps average download speed & 3.80 Mbps average upload speed across measured routes for highway drive. (refer table-57)

3. RJIL: Voice

- 100.00% call setup success rate and 0.47% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for LSA. (refer table-5)
- 100.00% call setup success rate and 0.61% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. (refer table-15)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all hotspot locations. (refer table-21)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for highway drive. (refer table-53)

Data

- RJIL has 228.60 Mbps average download speed & 27.43 Mbps average upload speed for LSA. (refer table-11)
- RJIL has 231.92 Mbps average download speed & 29.44 Mbps average upload speed across measured routes for city drive. (refer table-19)
- Gandhidham Railway Station, Hamirsar Lake & Lilashah Nagar Market have less download speed (less than 100 Mbps) out of total 9 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-34, 38 & 39)
- Gandhidham Bus Stand, Gandhidham Railway Station, GSRTC Anjar Bus Stand, Hamirsar Lake, Lilashah Nagar Market & Mundra Bus Stand have less upload speed (less than 20 Mbps) out of total 9 hotspot locations for auto-selection mode (5G/4G/3G/2G). (refer table-33, 34, 37, 38, 39 & 40)
- RJIL has 241.22 Mbps average download speed & 19.41 Mbps average upload speed across measured routes for highway drive. (refer table-57)

4. VIL: Voice

- 99.61% call setup success rate and 0.19% drop call rate have been observed in 3G/2G network mode for LSA. (refer table-3)
- 100.00% call setup success rate and 0.16% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for LSA. (refer table-5)
- 99.57% call setup success rate and 0.22% drop call rate have been observed in 3G/2G network mode for city drive. (refer table-13)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for city drive. (refer table-15)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for all hotspot locations. (refer table-21)
- 100.00% call setup success rate and 0.00% drop call rate have been observed in 3G/2G network mode for highway drive. (refer table-51)
- 100.00% call setup success rate and 1.82% drop call rate have been observed in auto-selection mode (5G/4G/3G/2G) for highway drive. (refer table-53)

Data

- VIL has 29.78 Mbps average download speed & 15.99 Mbps average upload speed for LSA. (refer table-11)
- VIL has 31.68 Mbps average download speed & 16.86 Mbps average upload speed across measured routes for city drive. (refer table-19)
- All locations have less download speed (less than 100 Mbps) for auto-selection mode (5G/4G/3G/2G). (refer table- 32 to 40)
- All hotspot locations have less upload speed (less than 20 Mbps) except GSRTC Anjar Bus Stand for auto-selection mode (5G/4G/3G/2G). (refer table- 32, 33, 34, 35, 36, 38, 39 & 40)
- VIL has 22.97 Mbps average download speed & 13.80 Mbps average upload speed across measured routes for highway drive. (refer table-57)

6. Annexure

6.1 Route wise coverage map

6.1.1 City




Figure-82: Signal strength 3G/2G network mode voice - AIRTEL.




Figure-83: Signal strength 3G/2G network mode voice - BSNL.




Figure-84: Signal strength 3G/2G network mode voice - VIL.




Figure-85: Signal strength auto-selection mode (5G/4G/3G/2G) voice - AIRTEL.




Figure-86: Signal strength auto-selection mode (5G/4G/3G/2G) voice - BSNL.




Figure-87: Signal strength auto-selection mode (5G/4G/3G/2G) voice - RJIL.




Figure-88: Signal strength auto-selection mode (5G/4G/3G/2G) voice - VIL.




Figure-89: Signal strength auto-selection mode (5G/4G/3G/2G) data - AIRTEL.




Figure-90: Signal strength auto-selection mode (5G/4G/3G/2G) data - BSNL.




Figure-91: Signal strength auto-selection mode (5G/4G/3G/2G) data - RJIL.




Figure-92: Signal strength auto-selection mode (5G/4G/3G/2G) data - VIL.

6.1.2 Highway

i) Bhuj to Bhachau



Figure-93: Signal strength 3G/2G network mode voice - AIRTEL.



Figure-94: Signal strength 3G/2G network mode voice - BSNL.




Figure-95: Signal strength 3G/2G network mode voice - VIL.




Figure-96: Signal strength auto-selection mode (5G/4G/3G/2G) voice - AIRTEL.




Figure-97: Signal strength auto-selection mode (5G/4G/3G/2G) voice - BSNL.




Figure-98: Signal strength auto-selection mode (5G/4G/3G/2G) voice - RJIL.



Figure-99: Signal strength auto-selection mode (5G/4G/3G/2G) voice - VIL.



Figure-100: Signal strength auto-selection mode (5G/4G/3G/2G) data - AIRTEL.




Figure-101: Signal strength auto-selection mode (5G/4G/3G/2G) data - BSNL.




Figure-102: Signal strength auto-selection mode (5G/4G/3G/2G) data - RJIL.



Figure-103: Signal strength auto-selection mode (5G/4G/3G/2G) data - VIL.

7. Appendix

The details of the setup used for conducting the drive test and the network or performance parameters captured under different conditions may be seen at Appendix-I. The calculation method of each QoS parameter is given in Appendix-II of the report. The summary of key equipment used in technical setup is as under

- **Device-1:** OnePlus Nord CE3 for 3G/2G CAT-15 Smartphone.
- **Device-2:** Samsung Galaxy S23 for 5G/4G/3G/2G CAT-20 Smartphone
- **Drive test Software:** Azenqos Engineering capable Applications to capture actual user experience.

7.1 Appendix-I

7.1.1 Drive test setup

Voice Call		
Call details	Technology	Detail
Call Setup Timeout	<ul style="list-style-type: none"> • 3G/2G auto mode- switch Call • 5G/4G/3G/2G auto mode- switch Call • 5G/4G MOS Call 	30 Sec
Call Duration		90/180 seconds
Wait/ Guard Time		15 Sec

Table-59: Voice test detail

Note-

- There is 15 sec wait time after locking and before starting first call in 3G/2G call.
- 10 calls to be made at each Hotspot location.
- Minimum 10 Calls to be made during the walk test. Call count will be increased based on walk test distance.
- Speech quality (MOS) has been measured only in city drive & highway by making Mobile to Mobile call.

Data Test		
Test Type	Technology	Detail
FTP/HTTP Download	5G/4G/3G/2G Auto Mode	500 MB File- 30 Sec Timeout, (Multithread 3- TCP Connection at a time)
FTP/HTTP Upload		250 MB File- 30 Sec Timeout, (Multithread 3- TCP Connection at a time)
YouTube Streaming		20 Sec Video & 25 sec Timeout (Only at Hotspot)
Web Browsing		3 popular websites (www.google.co.in , www.ircctc.co.in , www.sbi.bank.in) 20 sec timeout (only at Hotspot)

Latency & Jitter (TWAMP-UDP)		25 count- Dynamic 500 count- Hotspot Payload- 42 bytes in all drive
Packet Loss Rate (TWAMP-UDP & TCP)		500 counts (TWAMP-UDP) 500 counts (TCP) at each hotspot Payload- 42 bytes in all drive

Table-60: Data test detail

Note-

- 5 Data iteration to be done at each hotspot location.
- Minimum 5 iteration to be made during the walk test. Iteration count will be increased based on walk test distance.
- TWAMP-UDP & TCP test to be performed only once at hotspot location.
- Youtube & Web browsing test to be performed at static location only.
- All values are taken up to two decimal places with round off.
- Airtel server was used for FTP Download, FTP Upload, TCP and TWAMP testing, for Airtel
- Delhi-based TRAI server was used for HTTP Download, HTTP Upload, TCP and TWAMP testing, for BSNL.
- RJIL server was used for FTP Download, FTP Upload, TCP and TWAMP testing, for RJIL.
- VIL server was used for HTTP Download, HTTP Upload, TCP and TWAMP testing, for VIL.




Figure-104: Number of handsets used in city & highway drive

MO: Mobile originating

MT: Mobile terminating




Figure-105: Number of handsets used in railway/metro/walktest/hotspot/ coastal area

Note- 5G & 4G Lock mode testing has been performed at hotspot locations only.

7.1.2 Drive test Methodology

(a) Dynamic voice testing (on the move)




Figure-106: Voice test script for city/railway/metro/highway & coastal area

- 15 sec wait time is applied after locking Radio Access Technology (RAT) to 3G/2G and before starting first call in 3G/2G call.
- Speech quality (MOS) will be measured only City & Highway drive by making Mobile to Mobile calls.

(b) Hotspot voice testing



Figure-107: Voice test script for walktest/hotspot

- 10 calls to be made at each Hotspot location.
- Minimum 10 Calls to be made during the walk test. Call count will be increased based on walk test distance.

(c) Dynamic Data (internet) test




Figure-108: Data test script used in city/metro/railway/highway/walk test & coastal area

(d) Static Data(internet) testing




Figure-109: Data test script used at hotspot

- 5 Data iteration done at each hotspot location
- Min. 5 iteration made during the walk test.
- Web browsing duration mentioned above is for one web site only.
- One ping iteration (with 500 Count of each- TWAMP & TCP) done at hotspot location.

7.2 Appendix-II

7.2.1 Network Performance Parameters for Voice calls

Parameter Name	Definition
Call Setup Success Rate	<p>(i) Call Setup Success Rate is defined as the ratio of Established Calls to Call Attempts. 'Established Calls' mean the following events have happened in call setup:</p> <ul style="list-style-type: none"> (a) Call attempt is made (b) The signaling channel is allocated (c) The call is routed to the outwards path of the terminating network (d) An alert signal is received by caller in the form of ring back tone, busy tone, or an announcement. <p>CSSR = (Total Call Established/ Total Call Attempt) *100</p> <p>As per QoS Regulation 2024 benchmark value is >=98%</p>
Drop Call Rate	<p>Call drop represents the service provider network's ability to maintain a call once it has been successfully established. This parameter shall include both incoming calls and outgoing calls which, once they have been established and have an assigned traffic channel/ bearer, are dropped, or interrupted before their normal completion by the user, the cause of the early termination being within the service provider's network</p> <p>Drop Call Rate = (Total Call Drop/Total Call Established) *100</p> <p>As per QoS Regulation 2024 benchmark value is <=2%</p>
Call Setup Time	<p>Time taken from call initiate to call alerting/ringing.</p> <p>Call Setup Time = T2- T1</p> <p>T2- Ringing (VoLTE/VoNR) & Alerting (for WCDMA & GSM), T1- Invite (VoLTE/VoNR) & CM Service Request (for WCDMA & GSM)</p>
Voice Quality (MOS)	<p>Voice quality in mobile networks is measured with algorithms based on ITU-T P.863 (POLQA). The grading for Voice quality has been given as:</p> <p>Excellent: MOS ≥ 4 and < 5 Good : MOS ≥ 3 and < 4 Fair : MOS ≥ 2 and < 3 Poor : MOS ≥ 1 and < 2</p>
Handover Success Rate	<p>Handover Success Rate = Count of successful handovers (All Technology Handover combined) / Total count of Handover Attempt (All Technology Handover combined) *100</p> <p>Handover type which are considered- 2G Inter & Intra cell, 3G Soft & IRAT, 4G Inter & Intra frequency & SRVCC, 5G Inter & Intra frequency & 5G to 4G handovers.</p>
Silence Call	<p>A call which has ≥ 4 sec continuous RTP gap is considered as a Silence Call.</p> <p>Silence call rate = (count of silence call / Total calls established) *100</p> <p>If a call observes multiple silence count ≥ 4 sec in a particular established call it has been taken as one silent event.</p>

Jitter	<p>The inter arrival jitter is the difference in the relative transit time for two packets. The relative transit time is the difference between a packet's Real-time Transport Protocol (RTP) timestamp and the receiver's clock at the time of arrival, measured in the same units. If S_i is the RTP timestamp from packet i, and R_i is the time of arrival in RTP timestamps units for packet i, then for two packets i and j the inter-arrival jitter D can be expressed as:</p> $D(i,j) = (R_j - R_i) - (S_j - S_i)$ <p>The interarrival jitter is calculated continuously as each data packet i is received from source $SSRC_n$, using this difference D for that packet and the previous packet $i-1$ in order of arrival (not necessarily in sequence), according to the formula</p> $J(i) = J(i-1) + (D(i-1,i) - J(i-1))/16 \text{ or } 8$																																		
Downlink Packet Drop Rate	<p>Number of RTP (Real-time Transport Protocol) Packets lost divided by total RTP packet received (against each source_SSRC and sequence number) at call originating handset.</p> <p>This KPI is calculated from MOS call for packet call only (VoNR/VoLTE)</p>																																		
Uplink Packet Drop Rate	<p>Number of RTP (Real-time Transport Protocol) Packets lost divided by total RTP packet received (against each source_SSRC and sequence number) at call terminating handset. This KPI is calculated from MOS call for packet call only (VoNR/VoLTE).</p>																																		
Signal Strength	<p>Signal strength is the signal power level received by the wireless user.</p> <table><tr><th rowspan="2">Parameter Name</th><th rowspan="2">Technology</th><th colspan="4">Signal Strength (dBm)</th></tr><tr><th>Excellent</th><th>Good</th><th>Fair</th><th>Poor</th></tr><tr><td>Rx Level</td><td>GSM</td><td>0 to ≥ -65</td><td><-65 to ≥ -75</td><td><-75 to ≥ -85</td><td><-85 to min</td></tr><tr><td>RSCP</td><td>WCDMA</td><td>0 to ≥ -70</td><td><-70 to ≥ -80</td><td><-80 to ≥ -90</td><td><-90 to min</td></tr><tr><td>RSRP</td><td>LTE</td><td>0 to ≥ -80</td><td><-80 to ≥ -95</td><td><-95 to ≥ -110</td><td><-110 to min</td></tr><tr><td>SS_RSRP</td><td>NR</td><td>0 to ≥ -80</td><td><-80 to ≥ -95</td><td><-95 to ≥ -110</td><td><-110 to min</td></tr></table>	Parameter Name	Technology	Signal Strength (dBm)				Excellent	Good	Fair	Poor	Rx Level	GSM	0 to ≥ -65	<-65 to ≥ -75	<-75 to ≥ -85	<-85 to min	RSCP	WCDMA	0 to ≥ -70	<-70 to ≥ -80	<-80 to ≥ -90	<-90 to min	RSRP	LTE	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min	SS_RSRP	NR	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min
Parameter Name	Technology			Signal Strength (dBm)																															
		Excellent	Good	Fair	Poor																														
Rx Level	GSM	0 to ≥ -65	<-65 to ≥ -75	<-75 to ≥ -85	<-85 to min																														
RSCP	WCDMA	0 to ≥ -70	<-70 to ≥ -80	<-80 to ≥ -90	<-90 to min																														
RSRP	LTE	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min																														
SS_RSRP	NR	0 to ≥ -80	<-80 to ≥ -95	<-95 to ≥ -110	<-110 to min																														

Table-61: Network performance parameter and definition voice

7.2.2 Network Performance Parameters Data tests

Parameter Name	Definition
Download Speed (Mbps)	<p>The download speed is defined as the data transmission rate that is achieved for downloading a test file from a test server to a test device.</p> <p>Download Speed = Total bytes transferred during download / Total time for transfer</p> <ul style="list-style-type: none"> 80th percentile (upper range) & 20th percentile (lower range) value has been calculated for download throughput in dynamic drive and Hotspot combine data
Upload Speed (Mbps)	<p>The upload speed is the data transmission rate that is achieved for uploading a test file from a test device to a test server.</p> <p>Upload Speed = Total bytes transferred during upload / Total time for transfer.</p> <ul style="list-style-type: none"> 80th percentile (upper range) & 20th percentile (lower range) value has been calculated for upload throughput in dynamic drive and Hotspot combine data.
Download Session Setup Success Rate	<p>(total download session established (successfully connected to server)/ total download session attempt) *100.</p> <p>This KPI has been calculated for Hotspot only.</p>

Upload Session Setup Success Rate	(total upload session established (successfully connected to server)/ total upload session attempt)*100. This KPI need to report for Hotspot only.
Web Page Download Time	<p>Web browsing test is used to measure performance in terms of opening a web/HTTP page.</p> <p>Time taken to open the web page successfully is considered as web browsing delay/web page download time.</p>
Video Streaming Delay	The Video streaming delay is time taken from start of video transfer to First video frame displayed in player.
Latency (TWAMP-UDP)	<p>Latency is the time it takes for a small data set to be transmitted from a device to a server on the Internet and back to the same device again.</p> <p>The Latency is measured in milliseconds (ms).</p> <p>To calculate the one-way latency, we just do half of the round-trip time. 50th percentile of one-way latency has been reported.</p>
Jitter (TWAMP-UDP)	<p>Measure of variation in time in arrival of packets from a source to destination</p> <p>The consideration of packet delay jitter is considered by standard deviation of Inter Packet Delay Variation. If IPDV is used. By standard deviation is meant the average of standard deviation of IPDV on DL</p> <p>$IPDV(i) = D(i) - D(i-1)$ then Stdvs of IPDV is considered as jitter.</p>
Packet Loss Rate (TWAMP-UDP & TCP)	<p>Number of packets lost out of total packet transferred during test. Packet loss rate = (Total packet lost / Total packet sent) *100</p> <p>* Packet delay (using TWAMP-UDP & TCP) >90 ms considered as packet loss and included in packet loss rate.</p> <p>* Packet loss rate is calculated based on TWAMP-UDP & TCP.</p> <p>*90th percentile for Packet loss rate has been reported in overall Hotspot performance summary.</p>

Table-62: Network performance parameter and definition Data

Disclaimer: The observations presented above and, in the reports, represent the performance of the service providers on the area/route under test on the day/time of conducting the drive test and no inference whatsoever may be drawn regarding the quality of the telecom service by the service providers in the whole city/state/licensed service area.

Hardik
Rajeshbhai
Patel

Digitally signed by
Hardik Rajeshbhai
Patel
Date: 2026.09.28
19:49:14 +05'30'